



Product availability: Stock - Normally stocked in distribution facility



Main

Product	Double Throw Safety Switch
Current Rating	600 A
Certifications	UL listed
Enclosure Rating	NEMA 3R galvanized steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	3
Voltage Rating	240 V AC 250 V DC
Wire Size	250...500 kcmil copper or aluminium

Complementary

Width	621.28 mm (24.46 in)
Height	1608.07 mm (63.31 in)
Depth	225.55 mm (8.88 in)
Tightening torque	22.60 N.M (200 lbf.in) 31.07 N.M (275 lbf.in) 42.37 N.M (375 lbf.in) 56.49 N.m (500 lbf.in) 250...500 kcmil)

Ordering and shipping details

Category	00160 - DE1 MISC
Discount Schedule	DE1
GTIN	00785901786665
Package weight(Lbs)	102.97 kg (227 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty

18 months
