

Fittings

INSTALLATION COMPONENTS



CI319 Face Plate Extension – for thick walls



CF328 Plaster Guard – for use with 329 Mounting Plate Existing Home Inlet Kit



CF361 Mounting Bracket with plaster guard



CF363 90° Flanged EII – special for 3" walls



CF366 Straight Flange



CF369 45° Street EII



376UL 100' Wire 18/2
376500UL 500' Wire 18/2



379 Solvent Cement




CF382S 90° Sweep EII for use with Model 329 only for narrow walls



CF384 3-Way EII



CF387 45° Wye



392 Optional Muffler – reduces noise of currently installed power units



397 Wall Inlet Frame



CI324 2" Hose Clamp



CF329 Inlet Mounting Plate



CF361F Mounting Bracket with flanged spigot to assemble to any 382 series elbow




CF364 Flanged Tee



CF367 Flexible Tubing – 2" ID. x 36" vinyl over steel wire, interwoven with nylon cord, can be cut to any length



CF375 Utility Inlet – mounts on any flanged fitting; provides low-voltage contacts. Mounting box included.



CF377 90° Sweep EII-long



CF380 Pipe Support with wire clip



CF382XS Short 90° EII for installing VacPan™ where height is limited



CF385 45° EII




CF388 Stop Coupling



393 Metal Wall Cap – terminates exhaust discharge tube to outside



CI398 Blank Cover Plate w/screws CI398IV (Ivory), CI398WH (White)




326N Existing Home Inlet Kit



CI330 Exhaust Vent



CF362 90° Flanged EII – standard



CF365 Double-Flanged Tee




CF368 90° Street EII




376 100' Wire 18/2
376500 500' Wire 18/2



378 Nail Plate



CF382 90° Sweep EII



CF383 90° Tee




CF386 30° EII



CF389 End Cap



394 Blank Cover Plate – white; used in place of wall inlet in speculative rough-in installations



399 Extension Sleeve for floor or thick wall installations

METAL COMPONENTS – Zinc-coated/plated carbon steel for use in fire-walls to comply with fire codes.



300MTL Metal Tubing – 2" OD x 8', can be cut to size



301MTL 90° EII – Metal



302MTL Slip Coupling

CI3303RK Rough In – for 3-inlet installation includes:

3 – Mounting Brackets	1 – 90° Street EII	3 – 90° Tee Wyes
3 – Plaster Guards	1 – 45° Street EII	6 – Stop Couplings
6 – Screws for Plaster Guard	6 – Nail Guards	1 – Solvent Cement
3 – 90° Elbows	6 – 90° Sweep EIIs	1 – 1001 18/2 UL Wire
	2 – 45° EIIs	

CI3301RK Rough In – for 1-inlet installation includes:

1 – Mounting Bracket	1 – 90° Elbow	2 – 90° Sweep EIIs
1 – Plaster Guard	1 – 90° Street EII	1 – 45° EII
2 – Screws for Plaster Guard	1 – 45° Street EII	1 – 90° Tee Wye
	2 – Nail Guards	2 – Stop Couplings