



Product Number: 64706

Order Abbreviation: MP400/C/BU-ONLY

General Description: 400W METALARC PRO-TECH quartz metal halide lamp, EX39 base, BT37 bulb, open fixture rated, base up only, coated, 3400K

Product Information

Abbrev. With Packaging Info.	MP400CBUONLY 6/CS 1/SKU
ANSI Code	M59/O
ANSI Code 2	M59/O
Approx. Lumens (initial - vertical)	38500
Approx. Lumens (mean - vertical)	25000
Average Rated Life - Vertical (hr)	20000
Base	EX39 Exclusionary Mogul
Bulb	BT37
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3400
Diameter (in)	4.606
Diameter (mm)	117.00
Family Brand Name	Metalarc Pro-Tech®
Fixture Requirement	O
Hot Restrike Time (min)	7-12
Lamp Finish	Coated
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Voltage (V)	135.00
Nominal Wattage (W)	400.00
Operating Position	Base up within 15deg only
Warm-up Time (min)	2-4

Footnotes

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.