



Main

Product or component type	Industrial Control Transformer
Rated power in VA	100 VA
Primary voltage	208 V
Secondary voltage	120 V
Range of product	TF

Complementary

Network number of phases	1 phase
Rated power in VA	100 VA
Primary voltage	208 V : 120 V
Fuse type	CC 0.41 x 1.50 in top
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Height	4.18 in
Width	3.38 in
Depth	3.34 in
Material	Copper winding
Product compatibility	FSC1

Environment

product certifications	CE UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA degree of protection	Not rated (open device)
insulation temperature	105 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.