



## Range & Dryer Power Receptacles

3-Pole, 3-Wire Non-Grounding  
30A, 125/250V/AC  
50A, 125/250V/AC




10-30R

10-50R



14-30R

14-50R



32B



112



1258

### Features

- For replacement use in older homes with 3-Wire range and dryer connection points
- Heavy gauge galvanized steel mounting strap for corrosion resistance
- Flush receptacles fit one-gang or two-gang enclosures
- For use with copper or aluminum wire
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom

### Flush Power Receptacles



Rating		Description	Color	Catalog No.	
A	V/AC				
30	125/250	NEMA 10-30R Flush Mount Dryer Power Receptacle V/AC 124/250 Matching Plug S80	Brown	□ 38B	
50	125/250 124/250	NEMA 10-50R Flush Mount Range Power Receptacle Matching Plug S80	Brown	□ 32B	

cULus Listed to UL498 & UL943, file no. E60120; NOM certified

### Surface Power Receptacles



Rating		Description	Color	Catalog No.	
A	V/AC				
30	125/250 124/250	NEMA 10-30R Flush Mount Dryer Power Receptacle Matching Plug S80	Black	□ 125	
50	125/250 124/250	NEMA 10-50R Flush Mount Range Power Receptacle Matching Plug S80	Black	□ 112	

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified


### Flush Power Receptacles



Rating		Description	Color	Catalog No.	
A	V/AC				
30	125/250 124/250	NEMA 14-30R Flush Mount Dryer Power Receptacle Matching Plug S21	Black	□ 1257	
50	125/250 124/250	NEMA 14-50R Flush Mount Range Power Matching Plug S21	Black	□ 1258	

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

**Color Information:**  
B (Brown), BK (Black)



**Dimensional Information:** B-70 **Specification Information:** Please visit [www.cooperwiringdevices.com](http://www.cooperwiringdevices.com).  
Specifications and availability are subject to change without notice.

NAFTA Compliant - see page F-21