



Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	L

Complementary

[In] rated current	200 A
Number of poles	3
Poles description	3P
Breaking capacity	20 kA 250 V DC 125 kA 240 V AC 100 kA 480 V AC 50 kA 600 V AC 50 kA 500 V DC
[Ue] rated operational voltage	500 V DC 600 V AC
Continuous current rating	80 %
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 3/0...350 kcmil aluminium/copper
Phase connection	ABC
Magnetic hold current	1000 A
Magnetic tripping current	2000 A
Height	11.48 in
Width	4.48 in
Depth	5.87 in

Environment

product certifications	CCC CE CSA IEC UL listed
ambient air temperature for operation	40 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

