



Industrial Electrical Infrastructure

Preferred Parts – Middle East

PANDUIT[™]
infrastructure for a connected world

Industrial Electrical Infrastructure

Partner with a company committed to meeting the challenges you face when designing, installing and maintaining cabling infrastructures within heavy-duty industrial environments. Our global distribution, manufacturing, sales and technical support teams make Panduit solutions readily accessible, allowing the right products to be delivered when and where they are needed.

This catalog features the most common offering for heavy-duty industrial environments. For the complete offering, please contact your local Panduit representative or visit us at www.panduit.com/buildnow.



Table of Contents

| | |
|--|--------------|
| Computer Printables | 3 |
| Labeling Systems | 4 |
| Loose Piece Cable Ties | 5 – 6 |
| Stainless Steel Cable Ties and Permanent Identification | 6 – 7 |
| Terminals | 7 |

Computer Printables



| Part Number | Description | Std. Pkg. Qty. | Std. Ctn. Qty. |
|---------------|---|----------------|----------------|
| H200X034H1T | Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.34"H, White, 500 pieces. | 1 | — |
| H200X034H1T-B | Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.34"H, White, 2500 pieces. | 1 | — |
| H200X044H1T | Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.44"H, White, 500 pieces. | 1 | — |
| H200X044H1T-B | Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.44"H, White, 2500 pieces. | 1 | — |
| H200X064H1T | Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.64"H, White, 500 pieces. | 1 | — |
| H200X064H1T-B | Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.64"H, White, 500 pieces. | 1 | — |
| M300X050Y7T | Thermal transfer, marker plate, polyester/polyolefin, 3.00"W x 1.00"H, White. | 1 | 4 |
| M300X100Y6T | Thermal transfer, marker plate, polyester/polyolefin, 3.00"W x 1.00"H, Yellow. | 1 | 4 |
| M300X100Y7T | Thermal transfer, marker plate, polyester/polyolefin, 3.00"W x 1.00"H, White. | 1 | 4 |
| NWSLC-3Y | Orange cable identification sleeve for 3mm simplex cable, 1" length, 100 per pack. | 100 | 1000 |
| NWSLC-7Y | White cable identification sleeve for 3mm duplex fiber cable, 1" length, 100 per pack. | 100 | 1000 |
| PES197/E | Portable embossing system, 0.187" (4.77mm), 230 volts. | 1 | — |
| RMH4BL | Ribbon, hybrid, 4" wide, for use with TDP43MY and PTR2E, Black. | 1 | — |
| S050X075VATY | Thermal transfer, self-laminating label, vinyl, 0.50"W x 0.75"H, 0.25" print-on area, Clear/White, 3" core. | 5000 | 40000 |
| S100X150YAJ | Laser/inkjet, self-laminating label, polyester, 1.00"W x 1.50"L, 0.50" print-on area, Clear/White. | 2500 | 10000 |
| S100X160YAJ | Laser, self-laminating label, polyester, 1.00"W x 1.60"H, 0.80" print-on area, Clear/White. | 2500 | 10000 |
| S100X225YAJ | Laser, self-laminating label, polyester, 1.00"W x 2.25"L, 0.75" print-on area, Clear/White. | 1000 | 5000 |
| S100X400VA1Y | Thermal transfer, self-laminating label, vinyl, 1.00"W x 4.00"H, 1.00" print-on area, Clear/White, 1" core. | 1000 | 4000 |
| S200X150YAJ | Laser/inkjet, self-laminating label, polyester, 2.00"W x 1.50"H, 0.50" print-on area, Clear/White. | 1000 | 5000 |
| S200X225YAJ | Laser, self-laminating label, polyester, 2.00"W x 2.25"L, 0.75" print-on area, Clear/White. | 1000 | 5000 |
| TDP43ME/E | 300 dpi printer, including Easy-Mark™ Labeling Software and RMEH4BL hybrid ribbon. | 1 | — |



PES197/E



TDP43ME/E

Labeling Systems



Thermal Transfer Continuous Tape

| Part Number | Description | Std. Pkg. Qty. | Std. Ctn. Qty. |
|----------------|--|----------------|----------------|
| T400X000YK1 | Thermal transfer, continuous tape, polyester, 4.00"W x 100'L, Clear, 1" core. | 1 | 4 |
| T400X000VY1Y | Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Black, 1" core. | 1 | 4 |
| T400X000VX1Y | Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Yellow, 1" core. | 1 | 4 |
| T400X000VW1Y | Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Red, 1 inch core. | 1 | 4 |
| T400X000VU1Y | Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Orange, 1" core. | 1 | 4 |
| T400X000VS1Y | Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Green, 1" core. | 1 | 4 |
| T400X000VQ1Y | Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Blue, 1" core. | 1 | 4 |
| T400X000VP1Y | Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, White, 1" core. | 1 | 4 |
| T200X000YK1 | Thermal transfer, continuous tape, polyester, 2.00"W x 100'L, Clear, 1" core. | 1 | 4 |
| T200X000VY1Y | Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Black, 1" core. | 1 | 4 |
| T200X000VX1Y | Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Yellow, 1" core. | 1 | 4 |
| T200X000VW1Y | Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Red, 1" core. | 1 | 4 |
| T200X000VU1Y | Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Orange, 1" core. | 1 | 4 |
| T200X000VS1Y | Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Green, 1" core. | 1 | 4 |
| T200X000VQ1Y | Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Blue, 1" core. | 1 | 4 |
| T200X000VP1Y | Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, White, 1" core. | 1 | 4 |
| T100X000YK1 | Thermal transfer, continuous tape, polyester, 1.00"W x 100'L, Clear, 1" core. | 1 | 4 |
| T100X000VY1Y | Thermal transfer, continuous tape, vinyl, 1.00"W x 100'L, Black, 1" core. | 1 | 4 |
| T100X000VXC-BK | P1™ Cassette, continuous tape, vinyl, 1.00"W x 25'L, Yellow/Black. | 1 | 10 |
| T100X000VX1Y | Thermal transfer, continuous tape, vinyl, 1.00"W x 100'L, Yellow, 1" core. | 1 | 4 |
| T100X000VW1Y | Thermal transfer, continuous tape, vinyl, 1.00"W x 100'L, Red, 1" core. | 1 | 4 |
| T100X000VUC-BK | P1™ Cassette, continuous tape, vinyl, 1.00"W x 25'L, Orange/Black. | 1 | 10 |
| T100X000VU1Y | Thermal transfer, continuous tape, Vinyl, 1.00"W x 100'L, Orange, 1" core. | 1 | 4 |
| T100X000VS1Y | Thermal transfer, continuous tape, Vinyl, 1.00"W x 100'L, Green, 1" core. | 1 | 4 |
| T100X000VQ1Y | Thermal transfer, continuous tape, Vinyl, 1.00"W x 100'L, Blue, 1" core. | 1 | 4 |
| T100X000VPC-BK | P1™ Cassette, continuous tape, vinyl, 1.00"W x 25'L, Black on White. | 1 | 10 |
| T100X000VP1Y | Thermal transfer, Continuous Tape, Vinyl, 1.00"W x 100'L, White, 1" core. | 1 | 4 |
| T075X000VPC-BK | P1™ Cassette, continuous tape, vinyl, 0.75"W x 25'L, Black on White. | 1 | 10 |
| T050X000VXC-BK | P1™ Cassette, continuous tape, vinyl, 0.50"W x 25'L, Yellow/Black. | 1 | 10 |
| T050X000VPC-BK | P1™ Cassette, continuous tape, vinyl, 0.50"W x 25'L, Black on White. | 1 | 10 |
| T038X000VPC-BK | P1™ Cassette, continuous tape, vinyl, 0.38"W x 25'L, Black on White | 1 | 10 |
| T038X000FJC-BK | P1™ Cassette, continuous tape, polyolefin, 0.38"W x 25'L, White/Black. | 1 | 10 |
| S100X225VAC | P1™ Cassette, self-laminating label, vinyl, 1.00"W x 2.25"H, 0.75" print-on area, Clear/White. | 1 | 10 |
| S100X150VAC | P1™ Cassette, self-laminating label, vinyl, 1.00"W x 1.50"H, 0.50" print-on area, Clear/White. | 1 | 10 |
| S100X075VAC | P1™ Cassette, self-laminating label, vinyl, 1.00"W x 0.75"H, 0.25" print-on area, Clear/White. | 1 | 10 |
| R100X225V1C | P1™ Cassette, self-laminating label, vinyl, 1.00" W x 2.25" H, 0.75" print-on area, Clear/White | 1 | 10 |
| R100X150V1C | P1™ Cassette, Turn-Tell™ Self-Laminating Label, vinyl, 1.00"W x 1.50"H, 0.50" print-on area, Clear/White | 1 | 10 |
| M300X050Y6T | Thermal transfer, marker plate, polyester/polyolefin, 3.00"W x .50"H, Yellow. | 1 | — |
| M300X050Y6C | P1™ Marker Plate 3"W x 0.50"H, Yellow. | 1 | 10 |
| H200X084H2T | Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.84"H, Yellow, 500 pieces. | 1 | — |
| H200X044H2T | Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.44"H, Yellow, 500 pieces. | 1 | — |
| H100X034H1C | P1™ Cassette, heat shrink tubing, Military grade polyolefin, 1.00"W x 0.34"H, White. | 1 | 10 |
| H000X084H1C | P1™ Cassette, continuous heat shrink tubing, Military grade polyolefin, 6"W x 0.84"H, White. | 1 | 10 |
| H000X034H1C | P1™ Cassette, continuous heat shrink tubing, Military grade polyolefin, 8"W x 0.34"H, White. | 1 | 10 |
| F100X150AJC | P1™ Cassette, flag label, polyester, 1.00"W x 1.50"H. | 1 | 10 |
| C252X030FJC | P1™ Cassette, network label, adhesive polyolefin, 2.52"W x .30"H, White. | 1 | 10 |
| S8EQ-KIT-ACE | LS8EQ QWERTY hand-held thermal transfer printer kit with AC power adapter for Europe. | 1 | 2 |
| LS8EQ-KIT | QWERTY LS8EQ, printer kit. | 1 | 2 |
| LS8EQ | QWERTY LS8E, printer. | 1 | 4 |
| LS8E-KIT | LS8E, printer kit. | 1 | 2 |
| LS8E | LS8E, Printer | 1 | 4 |



LS8EQ-KIT

Loose Piece Cable Ties



PLT Ties



Barb Ties

| Part Number | Description | Std. Pkg. Qty. | Std. Ctn. Qty. |
|--------------|---|----------------|----------------|
| PLT3I-C0 | 11.4"L (290mm), Intermediate, weather resistant, Black. | 100 | 1000 |
| PLT3H-L0 | 11.4"L (290mm), Light-Heavy, weather resistant, Black. | 50 | 500 |
| PLT3S-C0 | 11.5"L (292mm) Standard, weather resistant, Black. | 100 | 1000 |
| PLT4I-C0 | 14.5"L (368mm), Intermediate, weather resistant, Black. | 100 | 1000 |
| PLT4H-L0 | 14.5"L (368mm), Light-Heavy, weather resistant, Black. | 50 | 500 |
| PLT4H-TL0 | 14.5"L (368mm), Light-Heavy, weather resistant, Black. | 250 | 2500 |
| PLT4S-M120 | 14.5"L (368mm), Standard, nylon 12, Black. | 1000 | 5000 |
| PLT4S-C0 | 14.5"L (368mm), Standard, weather resistant, Black. | 100 | 1000 |
| PLT4S-M0 | 14.5"L (368mm), Standard, weather resistant, Black. | 1000 | 5000 |
| PLT4.5S-C0 | 15.5"L (394mm), Standard, weather resistant, Black. | 100 | 1000 |
| PLT5S-M0 | 17.5"L (445mm), Standard, weather resistant, Black. | 1000 | 5000 |
| PLT5H-L0 | 17.7"L (450mm), Heavy, weather resistant, Black. | 50 | 500 |
| PLT6H-C0 | 20.9"L (530mm), Heavy, weather resistant, Black. | 100 | 1000 |
| PLT6H-L0 | 20.9"L (530mm), Heavy, weather resistant, Black. | 50 | 500 |
| PLT6LH-L0 | 21.9"L (556mm), Light-Heavy, weather resistant, Black. | 50 | 500 |
| PLT7LH-L0 | 24.7"L (627mm), Light-Heavy, weather resistant, Black. | 50 | 500 |
| PLT8LH-C120 | 27.6"L (701mm), Light-Heavy, nylon 12, Black. | 100 | 1000 |
| PLT8LH-L0 | 27.6"L (701mm), Light-Heavy, weather resistant, Black. | 50 | 500 |
| PLT1M-C | 3.9"L (99mm), Miniature, nylon, Natural. | 100 | 1000 |
| PLT1M-C0 | 3.9"L (99mm), Miniature, weather resistant, Black. | 100 | 1000 |
| PLT1M-M0 | 3.9"L (99mm), Miniature, weather resistant, Black. | 1000 | 50000 |
| PLT8H-C0 | 30.6"L (779mm), Heavy, weather resistant, Black. | 100 | 1000 |
| PLT1.5I-M30 | 5.6"L (142mm), Intermediate, heat stabilized, Black. | 1000 | 25000 |
| PLT1.5I-M120 | 5.6"L (142mm), Intermediate, nylon 12, Black. | 1000 | 25000 |
| PLT1.5I-M0 | 5.6"L (142mm), Intermediate, weather resistant, Black. | 1000 | 25000 |
| PLT1.5M-C0 | 5.6"L (142mm), Miniature, weather resistant, Black. | 100 | 1000 |
| PLT2S-M120 | 7.4"L (188mm), Standard, nylon 12, Black. | 1000 | 10000 |
| PLT2S-C0 | 7.4"L (188mm), Standard, weather resistant, Black. | 100 | 1000 |
| PLT2S-M0 | 7.4"L (188mm), Standard, weather resistant, Black. | 1000 | 10000 |
| PLT2M-C | 8.0"L (203mm), Miniature, nylon, Natural. | 100 | 1000 |
| PLT2M-C0 | 8.0"L (203mm), Miniature, weather resistant, Black. | 100 | 1000 |
| BT3I-C0 | Metal barb, 11.3"L (287mm), Intermediate, weather resistant, Black. | 100 | 1000 |
| BT3LH-L0 | Metal barb, 11.8"L (300mm), Light-Heavy, weather resistant, Black. | 50 | 500 |
| BT3S-C | Metal barb, 12.0"L (305mm), Standard, nylon, Natural. | 100 | 1000 |
| BT3S-C0 | Metal barb, 12.0"L (305mm), Standard, weather resistant, Black. | 100 | 1000 |
| BT4M-C0 | Metal barb, 14.2"L (361mm), Miniature, weather resistant, Black. | 100 | 1000 |
| BT4S-C0 | Metal barb, 15.1"L (384mm), Standard, weather resistant, Black. | 100 | 1000 |
| BT5LH-L0 | Metal barb, 18.1"L (460mm), Light-Heavy, weather resistant, Black. | 50 | 500 |
| BT7LH-C0 | Metal barb, 24.4"L (620mm), Light-Heavy, weather resistant, Black. | 100 | 1000 |
| BT7LH-L0 | Metal barb, 24.4"L (620mm), Light-Heavy, weather resistant, Black. | 50 | 500 |
| BT1M-C | Metal barb, 4.0"L (102mm), Miniature, nylon, Natural. | 100 | 1000 |
| BT1.5I-C0 | Metal barb, 6.1"L (155mm), Intermediate, weather resistant, Black. | 100 | 1000 |
| BT2M-C | Metal barb, 7.9"L (201mm), Miniature, nylon, Natural. | 100 | 1000 |
| BT2M-C0 | Metal barb, 7.9"L (201mm), Miniature, weather resistant, Black. | 100 | 1000 |
| BT2I-C0 | Metal barb, 8.0"L (203mm), Intermediate, weather resistant, Black. | 100 | 1000 |
| BT2I-M0 | Metal barb, 8.0"L (203mm), Intermediate, weather resistant, Black. | 1000 | 25000 |
| BT2S-C0 | Metal barb, 8.0"L (203mm), Standard, weather resistant, Black. | 100 | 1000 |

(continued on page 6)

Loose Piece Cable Ties (continued)



GS2B



GS4H



GTS

| Part Number | Description | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-----------------|--|----------------|----------------|
| P12-40-C | Nylon 6.6, 11.8"L, 0.87" maximum bundle diameter. | 100 | 1000 |
| P12-40-C0 | Weather resistant nylon 6.6, 11.8"L, 0.87" maximum bundle diameter. | 100 | 1000 |
| P12-50-C | Nylon 6.6, 11.8"L, 2.99" maximum bundle diameter. | 100 | 1000 |
| P12-50-C0 | Weather resistant nylon 6.6, 11.8"L, 2.99" maximum bundle diameter. | 100 | 1000 |
| P14-120-L | Nylon 6.6, 14.5"L, 4.02" maximum bundle diameter. | 50 | 500 |
| P14-120-L0 | Weather resistant nylon 6.6, 14.5"L, 4.02" maximum bundle diameter. | 50 | 500 |
| P14-40-C | Nylon 6.6, 14.6"L, 4.02" maximum bundle diameter. | 100 | 1000 |
| P14-40-C0 | Weather resistant nylon 6.6, 14.6"L, 4.02" maximum bundle diameter. | 100 | 1000 |
| P14-50-C | Nylon 6.6, 14.6"L, 4.02" maximum bundle diameter. | 100 | 1000 |
| P14-50-C0 | Weather resistant nylon 6.6, 14.6"L, 4.02" maximum bundle diameter. | 100 | 1000 |
| P4-18-C | Nylon 6.6, 3.9"L, 0.87" maximum bundle diameter. | 100 | 1000 |
| P4-18-C0 | Weather resistant nylon 6.6, 3.9"L, 0.87" maximum bundle diameter. | 100 | 1000 |
| P5-18-C | Nylon 6.6, 5.5"L, 1.30" maximum bundle diameter. | 100 | 1000 |
| P5-18-C0 | Weather resistant nylon 6.6, 5.5"L, 1.30" maximum bundle diameter. | 100 | 1000 |
| P5-40-C | Nylon 6.6, 5.5"L, 1.30" maximum bundle diameter. | 100 | 1000 |
| P5-40-C0 | Weather resistant nylon 6.6, 5.5"L, 1.30" maximum bundle diameter. | 100 | 1000 |
| P7-50-C | Nylon 6.6, 7.4"L, 1.81" maximum bundle diameter. | 100 | 1000 |
| P7-50-C0 | Weather resistant nylon 6.6, 7.4"L, 1.81" maximum bundle diameter. | 100 | 1000 |
| P8-18-C | Nylon 6.6, 7.9"L, 2.09" maximum bundle diameter. | 100 | 1000 |
| P8-18-C0 | Weather resistant nylon 6.6, 7.9"L, 2.09" maximum bundle diameter. | 100 | 1000 |
| P8-40-C | Nylon 6.6, 7.9"L, 2.09" maximum bundle diameter. | 100 | 1000 |
| P8-40-C0 | Weather resistant nylon 6.6, 7.9"L, 2.09" maximum bundle diameter. | 100 | 1000 |
| PC15-120-S25-L | Nylon 6.6, 15"L, 3.86" maximum bundle diameter. | 50 | 500 |
| PC15-120-S25-L0 | Weather resistant nylon 6.6, 15"L, 3.86" maximum bundle diameter. | 50 | 500 |
| PC8-50-S10-C | Nylon 6.6, 7.9"L, 1.97" maximum bundle diameter. | 100 | 1000 |
| PC8-50-S10-C0 | Weather resistant nylon 6.6, 7.9"L, 1.97" maximum bundle diameter. | 100 | 1000 |
| PM4-18-C | Nylon 6.6, 3.9"L, 0.71" maximum bundle diameter. | 100 | 1000 |
| PM7-50-C | Nylon 6.6, 7.5"L, 1.81" maximum bundle diameter. | 100 | 1000 |
| PR12-50-C | Nylon 6.6, 11.8"L, 2.99" maximum bundle diameter. | 100 | 1000 |
| PR12-50-C0 | Weather resistant nylon 6.6, 11.8"L, 2.99" maximum bundle diameter. | 100 | 1000 |
| PR8-50-C | Nylon 6.6, 7.9"L, 1.97" maximum bundle diameter. | 100 | 1000 |
| PR8-50-C0 | Weather resistant nylon 6.6, 7.9"L, 1.97" maximum bundle diameter. | 100 | 1000 |
| GS2B | Cable tie tool for Miniature, Intermediate, and Standard ties, adjustable tension. | 1 | — |
| GS4H | Cable tie tool for Standard, Heavy-Standard, Light-Heavy, and Heavy ties, adjustable tension. | 1 | — |
| GTS | Ergonomic cable tie tool for Subminiature, Miniature, Intermediate, and Standard ties, adjustable tension. | 1 | — |

Stainless Steel Cable Ties and Permanent Identification



MLT Ties

| Part Number | Description | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|---|----------------|----------------|
| MLT10H-LP | MLT tie, 304 stainless steel, Heavy, 33.0" (838mm), 0.010" (0.25mm) thickness. | 50 | 250 |
| MLT1S-CP | MLT tie, 304 stainless steel, Standard, 5.0" (127mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLT1S-CP316 | MLT tie, 316 stainless steel, Standard, 5.0" (127mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLT2.7S-CP | MLT tie, 304 stainless steel, Standard, 10.2" (259mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLT2S-CP | MLT tie, 304 stainless steel, Standard, 7.9" (201mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLT2S-CP316 | MLT tie, 316 stainless steel, Standard, 7.9" (201mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLT4H-LP | MLT tie, 304 stainless steel, Heavy, 14.3" (362mm), 0.010" (0.25mm) thickness. | 50 | 250 |
| MLT4S-CP | MLT tie, 304 stainless steel, Standard, 14.3" (362mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLT4S-CP316 | MLT tie, 316 stainless steel, Standard, 14.3" (362mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLT6H-LP | MLT tie, 304 stainless steel, Heavy, 20.5" (521mm), 0.010" (0.25) thickness. | 50 | 250 |

(continued on page 7)

Stainless Steel Cable Ties and Permanent Identification (continued)

| Part Number | Description | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-----------------|--|----------------|----------------|
| MLTC2H-LP316 | MLT tie, 316 stainless steel, selectively coated, Heavy, 7.9" (201mm), 0.010" (0.25mm) thickness. | 50 | 250 |
| MLTC4H-LP316 | MLT tie, 316 stainless steel, selectively coated, Heavy, 14.3" (362mm), 0.010" (0.25mm) thickness. | 50 | 250 |
| MLTC6H-LP316 | MLT tie, 316 stainless steel, selectively coated, Heavy, 20.5" (521mm), 0.010" (0.25mm) thickness. | 50 | 250 |
| MLTFC1.5S-CP316 | MLT tie, 316 stainless steel, fully coated, Standard. | 100 | 500 |
| MLTFC2S-CP316 | MLT tie, 316 stainless steel, fully coated, Standard, 7.9" (201mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLTFC4H-LP316 | MLT tie, 316 stainless steel, fully coated, Heavy, 14.3" (362mm), 0.010" (0.25mm) thickness. | 50 | 250 |
| MLTFC4S-CP316 | MLT tie, 316 stainless steel, fully coated, Standard, 14.3" (362mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLTFC5.4H-CP316 | MLT tie, 316 stainless steel, fully coated, Heavy, 18" (457mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MLTFC6H-LP316 | MLT tie, 316 stainless steel, fully coated, Heavy, 20.5" (521mm), 0.010" (0.25mm) thickness. | 50 | 250 |
| MLTFC8H-LP316 | MLT tie, 316 stainless steel, fully coated, Heavy, 26.8" (679mm), 0.010" (0.25mm) thickness. | 50 | 250 |
| MLTFC8S-CP316 | MLT tie, 316 stainless steel, fully coated, Standard, 26.8" (679mm), 0.010" (0.25mm) thickness. | 100 | 500 |
| MEHT187 | Metal tape embossing tool. | 1 | — |
| METS3-X | Embossing tape, 316 stainless steel, 0.5" X 21' (12.7mm x 6.4m). | 10 | 40 |
| METS4-X | Embossing tape, 304 stainless steel, 0.5" X 21' (12.7mm x 6.4m). | 10 | 40 |
| MMP350-C316 | Marker plate, 316 stainless steel, four-hole 3.5" x 0.75" x 0.010" (89mm x 19mm x 0.25mm) thickness. | 100 | 1000 |
| MMP350H-C | Marker plate, 304 stainless steel, four-hole, 3.5" x 0.75" x 0.010" (89mm x 19mm x 0.25mm) thickness. | 100 | 1000 |
| MMP350H-C316 | Marker plate, 316 stainless steel, four-hole, 3.5" x 0.75" x 0.010" (89mm x 19mm x 0.25mm) thickness. | 100 | 1000 |
| MMP350H-M316 | Marker plate, 316 stainless steel, four-hole, 3.5" x 0.75" x 0.010" (89mm x 19mm x 0.25mm) thickness. | 1000 | 4000 |
| ST2MT | Installation tool, MLT ties, twist cut off, Light-Heavy and Super-Heavy cross section. | 1 | — |
| GS4MT | Installation tool, MLT ties, controlled tension gun style, Standard. Light-Heavy, Heavy cross section. | 1 | — |



MEHT187



MMP350-C



ST2MT



GS4MT

Terminals

| Part Number | Description | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|--|----------------|----------------|
| PV18-6FX-MY | Fork terminal, expanded vinyl, 22 – 18 AWG, #6 stud size. | 1000 | 6000 |
| PV14-10F-C | Fork terminal, vinyl insulated, 16 – 14 AWG, #10 stud size. | 100 | 500 |
| PV14-8F-C | Fork terminal, vinyl insulated, 16 – 14 AWG, #8 stud size. | 100 | 500 |
| PV18-10F-MY | Fork terminal, vinyl insulated, 22 – 16 AWG, #10 stud size. | 1000 | — |
| PV18-8F-CY | Fork terminal, vinyl insulated, 22 – 16 AWG, #8 stud size. | 100 | 500 |
| PV10-8LF-L | Locking fork terminal, vinyl insulated, 12 – 10 AWG, #8 stud size. | 50 | 500 |
| PV14-6LF-M | Locking fork terminal, vinyl insulated, 18 – 14 AWG, #6 stud size. | 1000 | 6000 |
| PV14-8LF-M | Locking fork terminal, vinyl insulated, 18 – 14 AWG, #8 stud size. | 1000 | — |
| PV18-6LF-CY | Locking fork terminal, vinyl insulated, 22 – 18 AWG, #6 stud size. | 100 | 500 |
| PN10-10R-D | Ring terminal, nylon insulated, 12 – 10 AWG, #10 stud size. | 500 | — |
| PN10-6R-D | Ring terminal, nylon insulated, 12 – 10 AWG, #6 stud size. | 500 | — |
| PN10-38R-D | Ring terminal, nylon insulated, 12 – 10 AWG, 3/8" stud size. | 500 | — |
| PN10-56R-D | Ring terminal, nylon insulated, 12 – 10 AWG, 5/16" stud size. | 500 | 3000 |
| PN14-10R-M | Ring terminal, nylon insulated, 18 – 14 AWG, #10 stud size. | 1000 | — |
| PN14-8R-M | Ring terminal, nylon insulated, 18 – 14 AWG, #8 stud size. | 1000 | — |
| PN18-10R-M | Ring terminal, nylon insulated, 22 – 18 AWG, #10 stud size. | 1000 | — |
| PN18-14R-M | Ring terminal, nylon insulated, 22 – 18 AWG, #1/4 stud size. | 1000 | — |
| PN18-6R-M | Ring terminal, nylon insulated, 22 – 18 AWG, #6 stud size. | 1000 | — |
| PV10-10R-D | Ring terminal, vinyl insulated, 12 – 10 AWG, #10 stud size. | 500 | — |
| PV14-14R-M | Ring terminal, vinyl insulated, 16 – 14 AWG, #1/4 stud size. | 1000 | 6000 |



Fork Terminal



Locking Fork Terminal



Ring Terminal



PANDUIT™

Panduit CBC London
6 Broad Street Place
London
EC2M 7JH
UK
phone +44 (0) 208 601 7200

EMEA-CustomerServices@panduit.com
1-800-PANDUIT

www.panduit.com