



Main

Product or component type	Surge protection device
Range of product	Square D
Device short name	HEPD
Type of packing	Consumer packaging

Complementary

Surge current	50 kA per phase
[Ue] rated operational voltage	120/240 V AC
Phase	1 phase
Wiring configuration	3-wire (isolated ground)
[Uc] maximum continuous operating voltage	150 V
Line Rated Current	10 kA
Short-circuit protection	25 kA
Local signalling	1 LED green normal operation
Input voltage	600 V L - N 600 V L - G 1000 V L - L 900 V N - G
Height	82.04 mm (3.23 in)
Width	94.49 mm (3.72 in)
Depth	53.34 mm (2.10 in)

Environment

NEMA degree of protection	NEMA 4X
Standards	CSA C22.2 CUL UL 1449:ed. 4 type II
Ambient air temperature for operation	-31...149 °F (-35...65 °C)

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.