

PermaSleeve® Wire Marking Sleeves

www.BradyID.com

Single-Sided Printable, 2" Sleeve Width

(Continued from previous page.)

Catalog #	Color	Sleeves Per Roll	Approx. Wire Gauge	Range of Wire Diameter Inch (mm)		Supplied Diameter Inch (mm)	Recovered Diameter Inch (mm)	Recovered Wall Thickness Inch (mm)	Sleeve Width Inch (mm)	Rec. Printer	Rec. Ribbon
				Min.	Max.						
HX-750-2-WT	White	250	2 to 4/0	0.375 (9.5)	- 0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-750-2-WT-**	White	250	2 to 4/0	0.375 (9.5)	- 0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-750-2-WT-S	White	100	2 to 4/0	0.375 (9.5)	- 0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-750-2-WT-J	White	2,500	2 to 4/0	0.375 (9.5)	- 0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-750-2-WT-J-**	White	2,500	2 to 4/0	0.375 (9.5)	- 0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-1000-2-WT	White	250	2/0 to 0.950" dia.	0.450 (11.4)	- 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-1000-2-WT-**	White	250	2/0 to 0.950" dia.	0.450 (11.4)	- 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	--	PR Plus	R4300/ R6602
HX-1000-2-WT-S	White	100	2/0 to 0.950" dia.	0.450 (11.4)	- 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-1000-2-WT-J	White	2,500	2/0 to 0.950" dia.	0.450 (11.4)	- 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-1000-2-WT-J-**	White	2,500	2/0 to 0.950" dia.	0.450 (11.4)	- 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	--	PR Plus	R4300/ R6602
HX-1500-2-WT	White	250	N/A	0.750 (19.0)	- 1.400 (35.6)	1.500 (38.1)	0.752 (19.1)	0.040 (1.0) ± 0.006 (0.2)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-1500-2-WT-S	White	100	N/A	0.750 (19.0)	- 1.400 (35.6)	1.500 (38.1)	0.752 (19.1)	0.040 (1.0) ± 0.006 (0.2)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-1500-2-WT-J	White	1,000	N/A	0.750 (19.0)	- 1.400 (35.6)	1.500 (38.1)	0.752 (19.1)	0.040 (1.0) ± 0.006 (0.2)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-2000-2-WT	White	100	N/A	1.000 (25.4)	- 1.900 (48.3)	2.000 (50.8)	1.000 (25.4)	0.045 (1.1) ± 0.007 (0.2)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-2000-2-WT-S	White	50	N/A	1.000 (25.4)	- 1.900 (48.3)	2.000 (50.8)	1.000 (25.4)	0.045 (1.1) ± 0.007 (0.2)	2.000 (50.8)	PR Plus	R4300/ R6602
HX-2000-2-WT-J	White	1,000	N/A	1.000 (25.4)	- 1.900 (48.3)	2.000 (50.8)	1.000 (25.4)	0.045 (1.1) ± 0.007 (0.2)	2.000 (50.8)	PR Plus	R4300/ R6602

*Choosing Your PermaSleeve Color

While white is a standard color, additional colored sleeves are available as stock parts as well. Simply replace "WT" with the abbreviation of the desired color to order.

Example: HX-094-150-WT-4 becomes HX-094-150-RD-4

Available Stock Colors:

WT = White BL = Blue GY = Gray PK = Pink VT = Violet
 BK = Black GR = Green OR = Orange RD = Red YL = Yellow

** Choosing Your PermaSleeve Pieces (optional):

While 1 or 2 markers per sleeve is standard, you may also choose to have each sleeve slit multiple times to produce multiple pieces. Simply replace the double asterisks (**) in the catalog number to fill in your desired pieces per marker.


Example: HX-187-150-WT-** becomes HX-187-150-WT-4
 This "4" means that this 2.000" sleeve is slit into four 0.500" pieces.

Standard Option:


1 or 2 markers per sleeve

Other Available Slit Options:


3 or 4 markers per sleeve




WT = White




YL = Yellow




BK = Black




BL = Blue



GR = Green



GY = Gray



OR = Orange



PK = Pink



RD = Red



VT = Violet



Can't Find The PermaSleeve You Need? Build Your Own Part Number!

Use the "Assemble Your Own PermaSleeve" guide on page 176 to quickly and easily assemble the right B-7642 PermaSleeve HX Wire Marking Sleeve for your application.

Need additional help? Contact Brady Customer Service at 1-888-272-3946 for more information or to order.

Follow the steps on page 176 to quickly identify:

- Single or Double Sided Sleeves
- Sleeve Width
- Wire Diameter Requirements
- Color & Roll Size
- Additional Slits

Approx. wire gauge based on AWG for THHN wire.

View the Material Brands & Attributes Guide on page 4.

Benchtop Printer Ribbons on page 184.

Full Material Properties on page 187.

1-888-272-3946 | www.BradyID.com