

CH362DSWC

60A 3P Type4/4X 600V Heavy Duty Fusible Safety Switch, Window, Crouse-Hinds



Main

Range of product	Square D
Product or component type	Receptacle Switch
Product destination	Wiring connection APJ6485 Crouse-Hinds Arktite
[In] rated current	60 A
NEMA degree of protection	NEMA 3/3R/4/4X/5/12 stainless steel 304
Motor power hp	50 hp 600 V AC 30 hp 480 V AC
Disconnecter device type	Fusible disconnect
Short-circuit current	10 kA <= 200 kA
Device mounting	Surface
Number of poles	3
Network number of phases	3 phases
Electrical connection	Receptacle
Product certifications	CSA
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 12...AWG 2 (aluminium) AWG 14...AWG 2 (copper)
Wiring configuration	4-wire

Complementary

Environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.