


**Product datasheet**  
Characteristics

# NQ484L6C

NQ Pnlbrd Interior 600A, 3 PH, 4 Wire, 84 CCT, Mn Lug, Cu



## Main

Load center type	Main lugs
Circuit breaker type	QOB QOB-VH QHB
Material	Copper

## Complementary

Number of spaces	84
Enclosure nominal height	80 in
Enclosure nominal width	20 in
Enclosure nominal depth	5.75 in For NEMA 1 enclosure 6.5 in For NEMA 3R/5/12 enclosure
[In] rated current	600 A
Wiring configuration	4-wire
Network number of phases	3 phases
[Ue] rated operational voltage	240 V AC 48 V DC

## Environment

standards	CSA UL
-----------	-----------

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1419 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.