

# PermaSleeve® Wire Marking Sleeves

www.BradyID.com

3" Core Wire & Cable Materials:

## B-7642 PermaSleeve® Single-Sided Polyolefin Wire Marking Sleeves:

Use the table below to browse all available single-sided printing, 2" width B-7642 PermaSleeve® HX Polyolefin Wire Marking Sleeves or build your own catalog number on page 176.

### Single-Sided Printable, 2" Sleeve Width

Catalog #	Color	Sleeves Per Roll	Approx. Wire Gauge	Range of Wire Diameter Inch (mm) Min. Max.	Supplied Diameter Inch (mm)	Recovered Diameter Inch (mm)	Recovered Wall Thickness Inch (mm)	Sleeve Width Inch (mm)	Rec. Printer	Rec. Ribbon
HX-094-2-WT	White	2,500	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	0.020 (0.5) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-094-2-WT-**	White	2,500	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	0.020 (0.5) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-094-2-WT-S	White	500	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	0.020 (0.5) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-094-2-WT-J	White	10,000	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	0.020 (0.5) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-094-2-WT-J-**	White	10,000	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	0.020 (0.5) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-125-2-WT	White	2,500	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	0.020 (0.5) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-125-2-WT-**	White	2,500	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	0.020 (0.5) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-125-2-WT-S	White	500	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	0.020 (0.5) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-125-2-WT-J	White	10,000	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	0.020 (0.5) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-125-2-WT-J-**	White	10,000	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	0.020 (0.5) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-187-2-WT	White	2,500	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	0.020 (0.5) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-187-2-WT-**	White	2,500	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	0.020 (0.5) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-187-2-WT-S	White	500	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	0.020 (0.5) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-187-2-WT-J	White	10,000	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	0.020 (0.5) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-187-2-WT-J-**	White	10,000	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	0.020 (0.5) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-250-2-WT	White	1,000	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-250-2-WT-**	White	1,000	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-250-2-WT-S	White	250	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-250-2-WT-J	White	7,500	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-250-2-WT-J-**	White	7,500	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-375-2-WT	White	1,000	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-375-2-WT-**	White	1,000	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-375-2-WT-S	White	250	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-375-2-WT-J	White	2,500	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-375-2-WT-J-**	White	2,500	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-500-2-WT	White	500	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-500-2-WT-**	White	500	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602
HX-500-2-WT-S	White	250	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-500-2-WT-J	White	2,500	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2,000 (50.8)	PR Plus	R4300/ R6602
HX-500-2-WT-J-**	White	2,500	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus	R4300/ R6602

Single-Sided Printable, 2" Sleeve Width Sleeves continue on next page.

#### \*Choosing Your PermaSleeve Color

While white is a standard color, additional colored sleeves are available as stock parts as well. Simply replace "WT" with the abbreviation of the desired color to order.

Example: HX-094-150-WT-4 becomes HX-094-150-RD-4

#### Available Stock Colors:

WT = White    BL = Blue    GY = Gray    PK = Pink    VT = Violet  
 BK = Black    GR = Green    OR = Orange    RD = Red    YL = Yellow

#### \*\* Choosing Your PermaSleeve Pieces (optional):

While 1 or 2 markers per sleeve is standard, you may also choose to have each sleeve slit multiple times to produce multiple pieces. Simply replace the double asterisks (\*\*) in the catalog number to fill in your desired pieces per marker.

Example: HX-187-150-WT-\*\* becomes HX-187-150-WT-4  
 This "4" means that this 2,000" sleeve is slit into four 0.500" pieces.

#### Standard Option:

1 or 2 markers per sleeve

#### Other Available Slit Options:

3 or 4 markers per sleeve

