


GRX-PCBL346S Cable

Plenum rated cable for use with the following Lutron systems:

- GRAFIK Eye
- Energi Savr Node
- Quantum
- myRoom
- HomeWorks QS
- Plenum rated for use in ceilings and enclosures that are also used by the building air distribution system to transport environmental air.

Specifications

- Model number:
GRX-PCBL-346S-500 – 500 ft (150 m) spool
- Listed as type CL3P (Class 3 Plenum Cable) or CMP cULus.
- Five conductors:
 - Common – 18 AWG (0.75 mm²)
 - Power – 18 AWG (0.75 mm²)
 - MUX Data – 22 AWG (0.25 mm²)
 - MUX Data – 22 AWG (0.25 mm²) } Twisted wire pair
 - Drain Wire – 24 AWG (0.2 mm²)
- Total Outer Jacket Diameter: 0.17 in (4.37 mm).
- 300 V Rated.
- Plenum sheath, 75 °C rated.
- UL Listed.
- Rated FT6.
- cULus or CSA Listed.
- CPR Classification: E_{CA}
- Capacitance of 22 AWG (0.25 mm²) Twisted Wire Pair:
 - Conductor to shield: 48 pf/ft max
 - Conductor to Conductor: 25 pf/ft max



Note: Control link wiring distance maximums and other limitations for GRX-PCBL-346S cable are the same as those for GRX-CBL-346S cable. Please refer to the Product Specification Submittal Sheets or Product Installation Guides at www.lutron.com for details.

Lutron, Lutron, GRAFIK Eye, GRAFIK 6000, Softswitch128, HomeWorks, and Quantum are trademarks of Lutron Electronics Co., Inc., registered in the U.S. and other countries. Energi Savr Node, GRAFIK 5000, GRAFIK 7000, HomeWorks Interactive, myRoom, and LCP128 are trademarks of Lutron Electronics Co., Inc.

LUTRON SPECIFICATION SUBMITTAL

Page

Job Name:


Model Numbers:

Job Number:

GRX-PCBL-46L Cable

Plenum rated cable for use with the following Lutron systems:

- GRAFIK Eye 4000
 - LCP128
 - Softswitch128
 - GRAFIK 5000
 - GRAFIK 6000
 - GRAFIK 7000
 - Quantum
 - HomeWorks Interactive
 - HomeWorks QS
 - Energi Savr Node
- Plenum rated for use in ceilings and enclosures that are also used by the building air distribution system to transport environmental air.



Specifications

- Model numbers:
 - GRX-PCBL-46L-250 – 250 ft (75 m) spool
 - GRX-PCBL-46L-500 – 500 ft (150 m) spool
- Listed as type CL3P (Class 3 Plenum Cable) or CMP cULus.
- Six conductors:
 - Common – 12 AWG (4.0 mm²)
 - Power – 12 AWG (4.0 mm²)
 - MUX Data – 22 AWG (0.25 mm²)
 - MUX Data – 22 AWG (0.25 mm²) } Twisted wire pair
 - Sense Line – 18 AWG (0.75 mm²)
 - Drain Wire – 24 AWG (0.2 mm²)
- Total Outer Jacket Diameter: 0.30 in (7.75 mm).
- 300 V Rated.
- Plenum sheath, 75 °C rated.
- UL Listed.
- Rated FT6.
- cULus or CSA Listed.
- CPR Classification: E_{CA}
- Capacitance of 22 AWG (0.25 mm²) Twisted Wire Pair:
 - Conductor to shield: 48 pf/ft max
 - Conductor to Conductor: 25 pf/ft max

Note: Control link wiring distance maximums and other limitations for GRX-PCBL-46L cable are the same as those for GRX-CBL-46L cable. Please refer to the Product Specification Submittal Sheets or Product Installation Guides at www.lutron.com for details.

| | |
|--------------------|-----------------------|
| Job Name: | Model Numbers: |
| Job Number: | |