

Product data sheet

Characteristics

8903SMO12V02

lighting contactor, mechanically held, 30 A, 4 pole, open, 120/110V 60/50Hz

Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|---------|--------------------------------------|
| Product | Mechanically Held Lighting Contactor |
| Type | S |

Complementary

| | |
|-------------------------|----------------------------------|
| Control Circuit Voltage | 120 V AC 60 Hz 110 V AC 50 Hz |
| Current Rating | 30 A |
| Number of Poles | 4P |
| Control Units | No control units |
| Pilot Light | Without pilot light |
| Auxiliary Contacts | Without |
| Other Options | None |
| Electrical connection | Lugs |
| Height | 6.02 in (153 mm) |
| Depth | 4.69 in (119 mm) |
| Width | 4.53 in (115 mm) |

Environment

| | |
|------------------------|--------------------------------------|
| Enclosure Type | Not rated (open device) surface none |
| Product certifications | UL listed CSA |

Ordering and shipping details

| | |
|---------------------|--------------------------------|
| Category | 21324 - 8903 S (NOT S*C) MECH. |
| Discount Schedule | CP1 |
| GTIN | 00785901102465 |
| Package weight(Lbs) | 3.06 kg (6.75 lb(US)) |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|---------------------------|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Di(2-ethylhexyl)phthalate (DEHP) which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

Warranty

18 months
