

## Options

Product # Kit	Price	Description
<b>OSR-NA Series</b>		
ECA-JB1-NA	292.00	Junction box with power connection and termination for single connection c/w label and fastener
ECA-JB2-NA	414.00	Junction box with power connection and termination for double connection c/w label and fastener
EL-CLIC-P	223.00	Quick connector with supply lead, for 1 to 3 cables
EL-CLIC-S	212.00	Quick connector for direct connection or cold lead connection of 1 to 3 cables
EL-ECN-EX <sup>1</sup>	20.00	End termination for ELSR-NA
EL-SPN-16	31.00	Heat shrink splice-kit suitable for ELSR-NA and cold lead connections
ELAK-3-7	514.00	Junction box with mounting stand for non-hazardous (ordinary) and hazardous locations
ELVB-SRAN	38.00	Power connection without cable gland
ELVB-SRAN-12-PA	52.00	Power connection with plastique/PA12 cable gland/fitting, 1/2" NPT, non-hazardous location
ELVB-SRAN-34-PA	55.00	Power connection with plastique/PA12 cable gland/fitting, 3/4" NPT, non-hazardous location
ELVB-SRAN-34-ST	66.00	Power connection with steel/zinc cable gland/fitting, 3/4" NPT, non-hazardous location
ELVB-SREX-34-HT <sup>1</sup>	177.00	Power connection with nickel plated cable gland, 3/4" NPT, hazardous location
ELVB-SREX-M20-HT <sup>1</sup>	165.00	Power connection with nickel plated cable gland, M20, hazardous location
KIT-OSR-ELSR-NA	76.00	End and power termination kit with warning sticker NA Series
<b>OSR-MA Series (AO and BO outer jacket)</b>		
EL-ECM <sup>1</sup>	20.00	End termination for ELSR-MA
ELVB-SRAM	38.00	Power connection without cable gland
ELVB-SRAM-34-ST	66.00	Power connection with steel/zinc cable gland/fitting, 3/4" NPT, non-hazardous location
KIT-OSR-ELSR-MA	76.00	End and power termination kit with warning sticker MA Series
<b>OSR-MA Series (BF outer jacket)</b>		
EL-ECMF <sup>2</sup>	28.00	End termination for ELSR-MA-BF
ELVB-SRAM-34-ST	66.00	Power connection with steel/zinc cable gland/fitting, 3/4" NPT, non-hazardous location
KIT-OSR-ECA-MABF-PH-FIT	44.00	Brass gland cable fitting 3/4" NPT non-hazardous location for MA-BF cable
KIT-OSR-ELSR-MA-BF	85.00	End and power termination kit with warning sticker BF Series
KIT-OSR-MABF-PH-1-CTSOD <sup>3</sup>	83.00	Quick connect plumbing kit for 1" OD polyethylene CTS pipes for MA-BF cable
KIT-OSR-MABF-PH-114-CTSOD <sup>3</sup>	98.00	Quick connect plumbing kit for 1 1/4" OD polyethylene CTS pipes for MA-BF cable
KIT-OSR-MABF-PH-112-CTSOD <sup>3</sup>	127.00	Quick connect plumbing kit for 1 1/2" OD polyethylene CTS pipes for MA-BF cable
KIT-OSR-MABF-PH-34-ID <sup>3</sup>	76.00	Quick connect plumbing kit for 3/4" ID polyethylene pipes for MA-BF cable
KIT-OSR-MABF-PH-1-ID <sup>3</sup>	98.00	Quick connect plumbing kit for 1" ID polyethylene pipes for MA-BF cable
KIT-OSR-MABF-PH-114-ID <sup>3</sup>	111.00	Quick connect plumbing kit for 1 1/4" ID polyethylene pipes for MA-BF cable
KIT-OSR-MABF-PH-112-ID <sup>3</sup>	177.00	Quick connect plumbing kit for 1 1/2" ID polyethylene pipes for MA-BF cable
<b>OSR-WA Series</b>		
EL-CLIC-P	223.00	Quick connector with supply lead, for 1 to 3 cables
EL-CLIC-S	212.00	Quick connector for direct connection or cold lead connection of 1 to 3 cables
EL-ECW <sup>1</sup>	20.00	End termination for ELSR-WA
ELVB-SRAW	45.00	Power connection without cable gland
ELVB-SRAW-34-ST	72.00	Power connection with steel/zinc cable gland, 3/4" NPT, non-hazardous location
KIT-OSR-ELSR-WA	81.00	End and power termination kit with warning sticker WA Series
<b>OSR-HA Series</b>		
ECA-JB1-HA	292.00	Junction box with power connection and termination for single connection c/w label and fastener
ECA-JB2-HA	414.00	Junction box with power connection and termination for double connection c/w label and fastener
EL-ECH-EX <sup>1</sup>	20.00	End termination for ELSR-HA
ELAK-3-7	514.00	Junction box with mounting stand for non-hazardous (ordinary) and hazardous locations
ELVB-SRAH	38.00	Power connection without cable gland
ELVB-SRAH-34-ST	66.00	Power connection with steel/zinc cable gland/fitting, 3/4" NPT, non-hazardous location
ELVB-SREX-34-HT <sup>1</sup>	177.00	Power connection with nickel plated cable gland, 3/4" NPT, hazardous location
ELVB-SREX-M20-HT <sup>1</sup>	165.00	Power connection with nickel plated cable gland, M20, hazardous location
KIT-OSR-ELSR-HA	76.00	End and power termination kit with warning sticker HA Series



EL-EC(x)



ELVB-SRA(x)



ELVB-SRA(x)-34-ST



KIT-OSR-ELSR-xx



KIT-OSR-MABF-PH-xx-CTSOD



KIT-OSR-MABF-PH-xx-ID



ECA-JB1

<sup>1</sup> Minimum installation temperature -45 °C (-49 °F).

<sup>2</sup> Minimum installation temperature -13 °C (-25 °F).

<sup>3</sup> Identifying the type of pipe is key to ensuring a simple and effective connection, Ouellet Canada is not responsible for incorrect pipe selection. No returns will be accepted.

Options

Product # Kit	Price	Description
<b>All OSR Series</b>		
<b>Multiple applications</b>		
ECA-TYS6-280	10.00	Stainless steel fastener 1/4" x 6" (6.8 mm x 152.4 mm)
ECA-TYS9-280	11.00	Stainless steel fastener 1/4" x 9" (6.8 mm x 228.6 mm)
ECA-TYS12-280	15.00	Stainless steel fastener 1/4" x 12" (6.8 mm x 304.8 mm)
ECA-TYS18-280	17.00	Stainless steel fastener 1/4" x 18" (6.8 mm x 457.2 mm)
ECA-TYS24-280	20.00	Stainless steel fastener 1/4" x 24" (6.8 mm x 609.6 mm)
KIT-OSR-EL-WS03	2.00	Warning label/sign bilingual (English / French)
<b>Roof and gutter</b>		
ELB-20	12.00	Downspout 90° mounting plate
ELB-21	15.00	Gutter mounting plate
ELB-RCLIP	38.00	Roof clips for cable, qty 25
<b>Pipe tracing</b>		
ELB-03	50.00	Self-adhesive glass fiber tape, max. temp. = 90 °C (194 °F), 50 m (165 ft.)
ELB-06C	38.00	Self-adhesive aluminum tape, max. temp. = 80 °C (176 °F), 50 m (165 ft.)

Controls

Product #	Price	Description
<b>Controller options for roof and gutter for de-icing</b>		
DS-2C <sup>1</sup>	642.00	Aerial mounted controller with sensor to detect humidity and temperature, 30A, 100V to 277V
DS-8C <sup>1</sup>	763.00	Aerial mounted controller with sensor to detect temperature and a sensor to detect humidity with 10 ft. (3 m) cable, 30A, 100V to 277V
DS-9C <sup>1</sup>	751.00	Aerial mounted controller with sensor to detect temperature and a sensor to detect humidity with 10 ft. (3 m) cable, 2 X 30A, 100V to 277V
EX-50	228.00	50 ft. (15 m) extension kit, with connection fittings for humidity sensor
CDP-2	259.00	Interior controller and display for DS products
ETO2 <sup>1</sup>	748.00	Dual-zone electronic controller, 3 X 16A, 120V to 240V
ETF-744-99	186.00	24V outdoor sensor for measuring temperature
ETOR-55	364.00	Gutter sensor to detect humidity with 33 ft. (10 m) cable
<b>Controller options for pipe tracing for use in non-hazardous (ordinary) locations</b>		
ECA-E55-R25HT <sup>1</sup>	924.00	SPDT, NEMA 4X thermostat in molded aluminum housing, 22A at 120/250/480V, with 10 ft. (3 m) stainless steel bulb and capillary
TPR-L1N-3X-Q10 <sup>1</sup>	440.00	SPDT, NEMA 4X thermostat in polycarbonate housing, 22A at 120/250/480V, with 3 ft. (1 m) tinned copper bulb and capillary
TPR-L1N-10X-Q10 <sup>1</sup>	573.00	SPDT, NEMA 4X thermostat in polycarbonate housing, 22A at 120/250/480V, with 10 ft. (3 m) tinned copper bulb and capillary
TRF115-005 <sup>1</sup>	151.00	SPDT, NEMA 4X thermostat, range -17 °C to 49 °C (0 °F to 120 °F), 25A at 120/208/240/277V, with 5 ft. (1.5 m) stainless steel bulb and capillary
TRF115-007 <sup>1</sup>	156.00	SPDT, NEMA 4X thermostat, range -35 °C to 38 °C (-30 °F to 100 °F), 25A at 120/208/240/277V, with 8 ft. (2.4 m) copper bulb and capillary
ELTC-14-RTD <sup>1</sup>	725.00	Digital temperature control 20A at 90-260V, including 3-wire RTD (Pt-100) sensing element is 5 x 50 mm with 5 m of fluoropolymer lead wires, range 0 °C to 250 °C (32 °F to 482 °F)
<b>Controller options for pipe tracing for use in non-hazardous (ordinary) and hazardous locations</b>		
TXR-L2S-10-Q10 <sup>1</sup>	1421.00	SPDT, explosion-proof, NEMA 4, 7 and 9 thermostat, in anodized aluminum housing, 22A at 120/250/480V, with 10 ft. (3 m) stainless steel bulb and capillary
TM-1SIH1-E5-RTD-A1	1838.00	TraceMate™ I GFCI electronic thermostat for single circuit at 120V
TM-1DIH2-E5-RTD-A1	2260.00	TraceMate™ I GFCI electronic thermostat for single circuit at 240/2080V
TM-2SIH1-E5-RTD	3119.00	TraceMate™ II GFCI electronic thermostat for dual circuit at 120V
TM-2DIH2-E5-RTD	3531.00	TraceMate™ II GFCI electronic thermostat for dual circuit at 240/2080V
MS-2101 <sup>2</sup>	3704.00	MasterTrace Single circuit electronic GFCI controller with double pole, 85V to 280V, 30A, with user interface
MS-2102 <sup>2</sup>	4281.00	MasterTrace Double circuit electronic GFCI controller with single pole, 120V or 277V, 30A, with user interface
RTD-7	343.00	RTD probe for MasterTrace controller
<b>Control panel options</b>		
OSR-4-240	4477.00	240V GFCI control panel with 2 x 4-pole contactors, controller ETO2 and transformer 240-120V
OSR-6-240	4969.00	240V GFCI control panel with 3 x 4-pole contactors, controller ETO2 and transformer 240-120V
OSR-8-240	5624.00	240V GFCI control panel with 4 x 4-pole contactors, controller ETO2 and transformer 240-120V
OSR-12-240	6661.00	240V GFCI control panel with 6 x 4-pole contactors, controller ETO2 and transformer 240-120V

<sup>1</sup> Requires a ground fault circuit interrupter (GFCI) in the electrical panel.

<sup>2</sup> Requires a RTD probe for MasterTrace controller (RTD-7).

