

# H221DS

## SW FUSIBLE 30A 2P NEMA4 4X 5 STAINLESS

Product availability: Stock - Normally stocked in distribution facility



### Main

Product	Single Throw Safety Switch
Current Rating	30 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 4/4X/5 stainless steel 304
Factory Installed Neutral	None
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Number of Poles	2
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	250 V DC 240 V AC
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper

### Complementary

Width	183.39 mm (7.22 in)
Height	379.22 mm (14.93 in)
Depth	129.79 mm (5.11 in)
Tightening torque	5.08 N.M (45 lbf.in) 0.02 in <sup>2</sup> (13.3 mm <sup>2</sup> ) AWG 6 4.52 N.M (40 lbf.in) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) AWG 8 3.95 N.m (35 lbf.in) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) AWG 14...AWG 10)

### Ordering and shipping details

Category	00010 - H&HU SW,2&3P,N4,SS,30-200A
Discount Schedule	DE1
GTIN	00785901023579
Package weight(Lbs)	6.05 kg (13.33 lb(US))
Returnability	Yes
Country of origin	US

### Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Approximate Dimensions

