

**Product datasheet**  
Characteristics

# NQSE342100S

NQ Panelboard Serv Entr 100A, 3 Phase, 42 CCT,  
Surface Mount, 14 in



## Main

Device short name	NQ
Product or component type	Load Centre

## Complementary

[In] rated current	100 A
[Ue] rated operational voltage	120/240 V AC
Device mounting	Surface
Number of circuits	42
Network number of phases	3 phases
Width	14 in

## Environment

product certifications	CULus
NEMA degree of protection	NEMA Type 1

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1419 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.