

LJA36400CU33X

POWERPACT L-FRAME, I-LINE CIRCUIT BREAKER, MICROLOGIC 3.3S, 400A, 3P, 600V, 25kA



Product availability: Stock - Normally stocked in distribution facility



Main

Product or component type	Circuit breaker
Range of product	PowerPact L
Trip Unit Type	Electronic, standard, Micrologic 3.3 S, LSI
Interrupt Code	J

Complementary

Protection technology	Current limiter
Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	65 KA 480 V AC 100 KA 240 V AC 25 kA 600 V AC
Voltage Rating	600 V AC
Continuous current rating	100 %
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
Wire Size	AWG 2/0...500 kcmil aluminium/copper)2
Terminal Type	AL600LS52K3
I-Line Phase Connection	ABC
Height	373.38 mm (14.7 in)
Width	150.88 mm (5.94 in)
Depth	167.89 mm (6.61 in)
Tightening torque	38.94...442.54 lbf.in (4.4...50 N.m) 0.11...0.37 in ² (70...240 mm ²) AWG 2/0...500 kcmil)

Environment

Product certifications	NMX CSA UL listed CE CCC
------------------------	--------------------------------------

Ordering and shipping details

Category	01118 - L ELEC TRIP I-LINE BREAKER/SW
Discount Schedule	DE2
GTIN	00785901093466
Package weight(Lbs)	8.45 kg (18.63 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------