



Product availability: Stock - Normally stocked in distribution facility



### Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip Unit Type	Magnetic
Rating Code	A
Options	Handle

### Complementary

Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	42 KA 120 V AC 42 KA 240 V AC 30 KA 480Y/277 V AC 30 KA 480 V AC 22 kA 600 V AC
[Ue] rated operational voltage	600 V AC
Mounting mode	Unit mount
Electrical connection	Lugs load Terminal line
Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	2000 A
Magnetic tripping current	4000 A
Operator profile	Short lever
Wiring configuration	3-wire
Height	279.40 mm (11 in)
Width	152.40 mm (6 in)
Depth	148.34 mm (5.84 in)

### Environment

Product certifications	IEC CSA UL listed
------------------------	-------------------------

### Ordering and shipping details

Category	00935 - LAL/LHL BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901650386
Package weight(Lbs)	7.17 kg (15.8 lb(US))
Returnability	Yes
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------