

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure Stainless steel – WM 8017.605

Date : Feb 6, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure Stainless steel – WM 8017.605 - WM201608N4

created: 06.02.2018 build on www.rittal.com/us-en



Product description

Material: Door: Stainless steel, all-round foamed-in PU seal
Housing and door: Stainless steel 1.4301 (AISI 304)
Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4X

Supply includes: Housing with door(s)
Left hand hinge
Mounting plate
Wall mounting blind-nuts

Product features

Dimensions: Height: 500 mm (20 ")
Width: 400 mm (16 ")
Depth: 210 mm (8.3 ")

Material thickness: Housing: 1.5 mm (0.06 ")
Door: 1.5 mm (0.06 ")
Mounting plate: 1.5 mm (0.06 ")

Mounting plate: Height: 475 mm (19 ")
Width: 354 mm (14 ")

Lock version: Quarter turn

Packaging unit: 1 pc(s).

Weight/packaging unit: 15 kg (33.1 lb.)

EAN: 83182

Approvals

Approvals: UL + C-UL
