

Product datasheet
Characteristics

LAL26400

2P 600VAC/250VDC 400A LAL FA/LA MOLDED CASE CIRCUIT BREAKER



Main

Product or component type	Circuit breaker
Trip unit technology	Thermal-magnetic

Complementary

[In] rated current	400 A
Poles description	2P
Breaking capacity	42 kA at 240 V AC 30 kA at 480 V AC 22 kA at 600 V AC 10 kA at 125 V DC 10 kA at 250 V DC
[Ue] rated operational voltage	250 V DC 600 V AC
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
AWG gauge	AWG 1...600 kcmil (aluminium/copper) 1 cable(s) AWG 1...250 kcmil (aluminium/copper) 2 cable(s)
Terminal identifier	AL400LA
Magnetic hold current	2000 A
Magnetic tripping current	4000 A
Height	11 in
Width	6 in
Depth	5.84 in

Environment

product certifications	CSA IEC UL listed
------------------------	-------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.