



Product availability: Stock - Normally stocked in distribution facility



### Main

Product or component type	Circuit breaker
Range of product	PowerPact L
Trip Unit Type	Electronic, standard, Micrologic 3.3, LI
Interrupt Code	D

### Complementary

Protection technology	Current limiter
Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	25 KA 240 V AC 18 KA 480 V AC 14 kA 600 V AC
Voltage Rating	600 V AC
Continuous current rating	80 %
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
Wire Size	AWG 3/0...500 kcmil aluminium/copper)2
Terminal Type	AL600LF52K3
I-Line Phase Connection	ABC
Height	373.38 mm (14.7 in)
Width	150.88 mm (5.94 in)
Depth	167.89 mm (6.61 in)
Tightening torque	38.94...442.54 lbf.in (4.4...50 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) AWG 3/0...500 kcmil)

### Environment

Product certifications	UL listed CCC CSA CE NMX
------------------------	--------------------------------------

### Ordering and shipping details

Category	01118 - L ELEC TRIP I-LINE BREAKER/SW
Discount Schedule	DE2
GTIN	00785901298632
Package weight(Lbs)	8.51 kg (18.77 lb(US))
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------