

## Metal Halide Systems

Metal halide systems are characterized by a white light, a long life, and are suitable for both indoor and outdoor applications. Metal halide lamps will perform equally well and maintain light output in both cold and warm applications!

STANDARD Metal Halide ballasts are individually packaged, contain universal mounting brackets, and are prewired to the capacitor or ignitor when needed.

## Pulse Start

Lamp watts (W)	ANSI code	Input volts (V)	Order code	Description	Type	Circuit type	Input power ANSI (W)	Max. input current (A)
39	M130	120	<b>16603</b>	BMH0035/39/120/C/HX/N	Core and coil	HX-HPF	54	0.35
50	M110	120 / 277 / 347	<b>62929</b>	BMH0050/TRITAP/C/HX/H/K/STD	Core and coil	HX-HPF	70	0.60 / 0.25 / 0.20
		120 / 277 / 347	<b>10067</b>	BMH0050/TRITAP/F/HX/H/STD	F-Can	HX-HPF	67	0.50 / 0.23 / 0.20
		120 / 208 / 240 / 277	<b>62940</b>	BMH0050/QUADTAP/C/HX/H/K/STD	Core and coil	HX-HPF	67	0.50 / 0.30 / 0.25 / 0.20
70	M98	120	<b>16604</b>	BMH0070ACL/N	Core and coil	HX-NPF	94	3.00
		120 / 277 / 347	<b>62930</b>	BMH0070/TRITAP/C/HX/H/K/STD	Core and coil	HX-HPF	93	0.80 / 0.40 / 0.30
		120 / 277 / 347	<b>10068</b>	BMH0070/TRITAP/F/HX/H/STD	F-Can	HX-HPF	94	0.66 / 0.30 / 0.23
		120 / 208 / 240 / 277	<b>62941</b>	BMH0070/QUADTAP/C/HX/H/K/STD	Core and coil	HX-HPF	93	0.70 / 0.45 / 0.35 / 0.35
100	M90	120 / 277 / 347	<b>62931</b>	BMH0100/TRITAP/C/HX/H/K/STD	Core and coil	HX-HPF	129	1.30 / 0.60 / 0.50
		120 / 277 / 347	<b>10069</b>	BMH0100/TRITAP/F/HX/H/STD	F-Can	HX-HPF	125	0.90 / 0.36 / 0.30
		120 / 208 / 240 / 277	<b>62942</b>	BMH0100/QUADTAP/C/HX/H/K/STD	Core and coil	HX-HPF	125	1.50 / 0.90 / 0.75 / 0.65
150	M102	120 / 277 / 347	<b>62932</b>	BMH0150/TRITAP/C/HX/H/K/STD	Core and coil	HX-HPF	188	1.85 / 0.85 / 0.70
		120 / 277 / 347	<b>10070</b>	BMH0150/TRITAP/F/HX/H/STD	F-Can	HX-HPF	185	1.50 / 0.70 / 0.55
		120 / 208 / 240 / 277	<b>10116</b>	BMH0150/QUADTAP/C/HX/H/K/STD	Core and coil	HX-HPF	185	2.95 / 1.75 / 0.45 / 0.30
175	M152	120 / 277 / 347	<b>59640</b>	BMHP0175/TRITAP/C/CWA/H STD	Core and coil	CWA	208	1.10 / 0.50 / 0.40
200	M136	120 / 277 / 347	<b>16624</b>	BMHP0200/TRITAP/C/CWA/H	Core and coil	CWA	232	1.15 / 0.50 / 0.40
250	M153	120 / 277 / 347	<b>59641</b>	BMHP0250/TRITAP/C/CWA/H STD	Core and coil	CWA	288	1.65 / 0.75 / 0.60
320	M154	120 / 208 / 240 / 277	<b>31366</b>	BMHP0320/QUADTAP/C/CWA/H	Core and coil	CWA	368	3.25 / 1.85 / 1.65 / 1.40
		120 / 277 / 347	<b>59642</b>	BMHP0320/TRITAP/C/CWA/H STD	Core and coil	CWA	368	1.60 / 0.70 / 0.55
350	M131	120 / 277 / 347	<b>16627</b>	BMHP0350/TRITAP/C/CWA/H	Core and coil	CWA	400	1.80 / 0.78 / 0.40
400	M155	120 / 208 / 240 / 277	<b>16628</b>	BMHP0400/QUADTAP/C/CWA/H	Core and coil	CWA	452	2.31 / 1.00 / 1.15 / 1.00
		120 / 277 / 347	<b>59639</b>	BMHP0400/TRITAP/C/CWA/H STD	Core and coil	CWA	452	2.35 / 1.05 / 0.85
450	M144	120 / 277 / 347	<b>16629</b>	BMHP0450/TRITAP/C/CWA/H	Core and coil	CWA	508	2.90 / 1.27 / 1.00
575	M178	120 / 277 / 347	<b>58971</b>	BMHP0575/TRITAP/C/HX/H	Core and coil	HX-HPF	635	10.05 / 3.15 / 3.00
875	M166	120 / 208 / 240 / 277	<b>57523</b>	BMHP0875/QUADTAP/C/CWA/HX	Core and coil	CWA	950	6.60 / 3.80 / 3.30 / 2.85
		120 / 277 / 347	<b>56523</b>	BMHP0875/TRITAP/C/CWA/H	Core and coil	CWA	940	6.50 / 2.85 / 2.25
1000	M141	120 / 277 / 347	<b>16732</b>	BMHP1000/TRITAP/C/CWA/H	Core and coil	CWA	1 080	7.55 / 3.25 / 2.60

# Magnetic HID Ballasts