



Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|------------------------------|-----------------------------------------|
| Product | Single Throw Safety Switch |
| Current Rating | 800 A |
| Certifications | UL listed file E2875 |
| Enclosure Rating | NEMA 1 steel |
| Factory Installed Neutral | Neutral (factory installed) |
| Disconnect Type | Fusible disconnect |
| Short Circuit Current Rating | 200 kA maximum L |
| Mounting Type | Surface |
| Number of Poles | 3 |
| Electrical Connection | Lugs |
| Duty Rating | Heavy duty |
| Voltage Rating | 600 V AC/DC |
| Wire Size | AWG 3/0...750 kcmil copper or aluminium |

Complementary

| | |
|-------------------|--------------------------------------------------------------------------------------------------------|
| Width | 930.15 mm (36.62 in) |
| Height | 1755.90 mm (69.13 in) |
| Depth | 450.85 mm (17.75 in) |
| Tightening torque | 42.37 N.m (375 lbf.in) 0.13...0.59 in ² (85.01...380 mm ²) AWG 3/0...750 kcmil) |

Ordering and shipping details

| | |
|---------------------|---------------------------------|
| Category | 00053 - H&HU SW,NEMA1,400-1200A |
| Discount Schedule | DE1 |
| GTIN | 00785901442417 |
| Package weight(Lbs) | 169.19 kg (373 lb(US)) |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------|-----------------------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Approximate Dimensions

