

Product datasheet
Characteristics

SDSA1175
Surge Protect - 36kA - 120/240VAC - 1P3W - T4X



Main

Product or component type	Surge protection device
Range of product	Square D

Complementary

Surge current	36 kA per phase
[Ue] rated operational voltage	120/240 V AC
Network number of phases	1 phase
Wiring configuration	3-wire
[Uc] maximum continuous operating voltage	150 V
Nominal discharge current	10 kA
Short-circuit protection	25 kA
Local signalling	Status LED, green = normal operation
Height	2.25 in
Width	2.25 in
Depth	2.7 in

Environment

NEMA degree of protection	NEMA 4X
enclosure material	Plastic, colour : black
standards	NEC 285 CSA C22.2 No 8 UL 1449 type I ed. 4
ambient air temperature for operation	65 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.