

**Product datasheet**  
Characteristics

# CH364

200A 3P Type1 600VAC/DC Heavy Duty Fusible Safety Switch



### Main

Product or component type	Single Throw Safety Switch
Disconnecter device type	Fusible disconnect
Number of poles	3
Electrical connection	Lugs
Series name	Heavy duty

### Complementary

[In] rated current	200 A
Device composition	None
Device mounting	Surface
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 6...250 kcmil (copper or aluminium)

### Environment

product certifications	CSA
NEMA degree of protection	NEMA 1 galvanized steel

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.