

Average Standard Watt Density Models 275W/ft.

Watts	Watts 240/208V	120V	Price	208V	Product #					Length		Weight	
					240/208V	Price	347V	600V	Price	in.	mm	lb	kg
300	300/225	OFM0302	78.00	OFM0308	OFM0300	62.75	-	-	-	22 5/16	566	4.5	2.0
500	500/375	OFM0502	82.50	OFM0508	OFM0500	65.25	OFM0507	-	77.00	27 3/16	691	5.5	2.5
750	750/563	OFM0752	95.50	OFM0758	OFM0750	75.25	OFM0757	OFM0756	91.00	37 3/16	945	7.3	3.3
1000	1000/750	OFM1002	111.00	OFM1008	OFM1000	88.00	OFM1007	OFM1006	106.50	47 1/2	1206	9.0	4.0
1250	1250/938	OFM1252	135.75	OFM1258	OFM1250	104.50	OFM1257	OFM1256	129.50	57	1447	10.5	4.8
1500	1500/1125	OFM1502	142.25	OFM1508	OFM1500	113.00	OFM1507	OFM1506	139.00	65 11/16	1668	12.0	5.5
1750	1750/1313	-	-	OFM1758	OFM1750	134.50	OFM1757	OFM1756	167.50	75	1905	13.5	6.2
2000	2000/1500	-	-	OFM2008	OFM2000	147.75	OFM2007	OFM2006	178.00	83 13/16	2128	15.0	6.8
2250 ¹	2250/1688 ¹	-	-	OFM2258	OFM2250	163.00	OFM2257	OFM2256	197.50	92 5/8	2353	16.5	7.5
2500 ¹	2500/1875 ¹	-	-	OFM2508	OFM2500	175.50	OFM2507	OFM2506	211.00	101 13/16	2585	18.0	8.2

Average Low Watt Density Models 200W/ft.

Watts	Watts 240/208V	120V	Price	208V	Product #					Length		Weight	
					240/208V	Price	347V	600V	Price	in.	mm	lb	kg
300	300/225	OFM0302-691	82.50	OFM0308-691	OFM0300-691	65.25	-	-	-	27 3/16	691	5.5	2.5
500	500/375	OFM0502-945	95.50	OFM0508-945	OFM0500-945	75.25	OFM0507-945	-	91.00	37 3/16	945	7.3	3.3
750	750/563	OFM0752-1206	111.00	OFM0758-1206	OFM0750-1206	88.00	OFM0757-1206	OFM0756-1206	106.50	47 1/2	1206	9.0	4.0
1000	1000/750	OFM1002-1447	135.75	OFM1008-1447	OFM1000-1447	104.50	OFM1007-1447	OFM1006-1447	129.50	57	1447	10.5	4.8
1250	1250/938	OFM1252-1668	142.25	OFM1258-1668	OFM1250-1668	113.00	OFM1257-1668	OFM1256-1668	139.00	65 11/16	1668	12.0	5.5
1500	1500/1125	OFM1502-2128	170.50	OFM1508-2128	OFM1500-2128	147.75	OFM1507-2128	OFM1506-2128	178.00	83 13/16	2128	15.0	6.8
1750 ¹	1750/1313 ¹	-	-	OFM1758-2353	OFM1750-2353	163.00	OFM1757-2353	OFM1756-2353	197.50	92 5/8	2353	16.5	7.5
2000 ¹	2000/1500 ¹	-	-	OFM2008-2585	OFM2000-2585	175.50	OFM2007-2585	OFM2006-2585	211.00	101 13/16	2585	18.0	8.2
2250 ¹	2250/1688 ¹	-	-	OFM2258-2585	OFM2250-2585	175.50	OFM2257-2585	OFM2256-2585	211.00	101 13/16	2585	18.0	8.2

Options

Product # Kit	Product # Factory installed*	Price	Description
KIT-OFM-CI	-	86.25	Corners (inside and outside)
KIT-OFM-DIS20	DIS20	133.50	Disconnect switch, double-pole, 20A at 250V max.
KIT-OFM-JT	-	40.25	Splice plate 3 9/16 in. (90 mm)
KIT-OFM-RO1	-	67.75	Baseboard section 6 in. (152 mm) - Surface-mount 5-15R receptacle - 15A at 120V
KIT-OFM-RO2	-	230.75	Baseboard section 6 in. (152 mm) - 240V splitter box toward a surface-mount, 6-20R receptacle (20A switch, double-pole, double-throw)
KIT-OFM-RO2B	-	187.00	Baseboard section 6 in. (152 mm) - Surface-mount 6-20R receptacle - 240V
KIT-OFM-R-347	R	71.75	Single-pole relay, coil 24V, without transformer, 22A at 120V, 208V, 240V - 18A at 347V
KIT-OFM-R-600	R	97.75	Single-pole relay, coil 24V, without transformer, 10A at 600V
KIT-OFM-RT-120	RT	121.25	Single-pole relay, coil 24V, with transformer 120V/24V, 22A at 120V
KIT-OFM-RT-208	RT	101.50	Single-pole relay, coil 24V, with transformer 208V/24V, 22A at 208V
KIT-OFM-RT-240	RT	101.50	Single-pole relay, coil 24V, with transformer 240V/24V, 22A at 240V
KIT-OFM-RT-277	RT	101.50	Single-pole relay, coil 24V, with transformer 277V/24V, 19A at 277V
KIT-OFM-RT-347	RT	101.50	Single-pole relay, coil 24V, with transformer 347V/24V, 18A at 347V
KIT-OFM-RT-600 ³	RT ³	145.75	Single-pole relay, coil 24V, with transformer 600V/24V, 10A at 600V (2-wire only)
KIT-OFM-240SPLITTER	-	100.50	Baseboard section 6 in. (152 mm) - 240V splitter box to permanently connect a secondary product (20A switch, double-pole, double-throw)
KIT-OFM-THA ⁵	THACD ⁵	60.00	Built-in electronic thermostat with rotary knob installed in the right junction box only: 12.5A at 120V, 208V, 240V
-	THCG ⁴	148.25	Baseboard section 6 in. (152 mm) with built-in electronic thermostat (240V only), installed at left end
KIT-OFM-SR	-	72.25	Baseboard section 6 in. (152 mm) for the installation of a 24V relay (relay not included)
KIT-OFM-TB6	TB6	38.75	Single-pole bi-metal thermostat: 25A at 120V, 208V, 240V, 277V - 10A at 347V, 480V, 600V
KIT-OFM-TB26 ²	TB26 ²	46.50	Double-pole bi-metal thermostat: 25A at 120V, 208V, 240V, 277V - 10A at 347V, 480V, 600V
KIT-OFM-TB6-AV	TB6AV	69.00	Single-pole bi-metal tamperproof thermostat: 25A at 120V, 208V, 240V, 277V - 10A at 347V, 480V, 600V
KIT-OFM-TB26-AV ²	TB26AV ²	71.25	Double-pole bi-metal tamperproof thermostat: 25A at 120V, 208V, 240V, 277V - 10A at 347V, 480V, 600V
KIT-OFM-TRIAC-347	TRIAC	71.00	Single-pole electronic relay, coil 24V, without transformer, 15A at 347V max.
KIT-OFM-TRIAC-347T	TRIACT	99.75	Single-pole electronic relay, coil 24V, with transformer, 15A at 208V, 240V, 277V, 347V
KIT-OFM-TRIAC-600	TRIAC	129.75	Single-pole electronic relay, coil 24V, without transformer, 10A at 600V max.

* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.

¹ These models must be ordered in pairs to reduce shipping damages.

² "Off" position.

³ These 2-wire relays with transformer can't supply of 3-wire low voltage thermostats.

⁴ The white and almond baseboard sections come with an integrated white thermostat. The integrated thermostat is black for all other colors.

⁵ Compatible with the devices manufactured after 14-10-2019 only.

Add "BL" for white, "AM" for almond. Upcharge available for optional colors shown in the color chart section.

Other voltages available upon request.