

Product datasheet
Characteristics

2510MCR3

Manual Starter - NEMA 7&9 - 3P - Size M1 - 600VAC



Main

Product or component type	Manual Starter
Range of product	M
NEMA size	M-1

Complementary

Control type	Push-button
Local signalling	No indicator
Motor power hp	7.5 hp at 200...230 V AC 3 phases 10 hp at 380...575 V AC 3 phases
[Ue] rated operational voltage	600 V AC
Poles description	3P
Motor starter type	Non reversing
Electrical connection	Pressure wire clamp
Thermal overload type	Melting alloy
Number of thermal units required	3
AWG gauge	AWG 14...AWG 8 (copper)
Auxiliary contact composition	Without
Height	10.5 in
Width	6 in
Depth	6.13 in

Environment

product certifications	UL listed file E58760 CCN NPXZ CSA LR26817 class 3218 04
NEMA degree of protection	NEMA 7/9 cast iron

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.