


TYPE TTGC

Features

- Manufactured from bronze
- Eye bolt on TTGC2 rotates to accommodate cable in vertical or horizontal direction
- Range taking
- Stud fits all standard EEI-NEMA distribution transformers

Benefits

- Provides maximum strength and superior conductivity
- Flexibility
- Permits inventories to be kept to a minimum
- Reliability



Catalog Number	Conductor Range		Stud Thread Size UNC - 2A	Dimensions		
	Max.	Min.		A	B	C
TTGC2	2/0	8 sol	1/2-13	1-51/64	1-9/64	1-21/32
TTGC3	1 str	10 sol	1/2-13	1-3/8	1-3/64	1-9/16
TTGC4+	1 str	10 sol	1/2-13	1-1/4	7/8	1-3/8
TTGC2TN+	2/0	8 sol	1/2-13	1-51/64	1-9/64	1-21/32
TTGC3TN*	1 str	10 sol	1/2-13	1-3/8	1-3/64	1-9/16
TTGC4TN*	1 str	10 sol	1/2-13	1-1/4	7/8	1-3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

+ RUS Listed

* Tin Plated


TYPE TTGC

Features

- Manufactured from bronze
- Eye bolt on TTGC2 rotates to accommodate cable in vertical or horizontal direction
- Range taking
- Stud fits all standard EEI-NEMA distribution transformers

Benefits

- Provides maximum strength and superior conductivity
- Flexibility
- Permits inventories to be kept to a minimum
- Reliability



Catalog Number	Conductor Range		Stud Thread Size UNC - 2A	Dimensions		
	Max.	Min.		A	B	C
TTGC2	2/0	8 sol	1/2-13	1-51/64	1-9/64	1-21/32
TTGC3	1 str	10 sol	1/2-13	1-3/8	1-3/64	1-9/16
TTGC4+	1 str	10 sol	1/2-13	1-1/4	7/8	1-3/8
TTGC2TN+	2/0	8 sol	1/2-13	1-51/64	1-9/64	1-21/32
TTGC3TN*	1 str	10 sol	1/2-13	1-3/8	1-3/64	1-9/16
TTGC4TN*	1 str	10 sol	1/2-13	1-1/4	7/8	1-3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

+ RUS Listed

* Tin Plated