

Programmable Controller Wiring Systems

Catalog Number Explanation, Continued

Pre-Wired Cable Cat. No. Explanation for Bulletin 1746 and 1769 Analog I/O Modules

Important: Use the following tables as a product configurator for pre-wired, IFM-ready, and I/O module-ready cables for Bulletins 1746, 1756, and 1771 digital I/O module cables. All combinations of these fields make valid product cat. nos. Refer to selection tables for IFM/XIM compatibility, additional cables, and ordering.

1492 – ACAB 005 A46

a *b* *c*

a

Analog Interface Cables

b

Standard or Build-to-Order Length Cable		
Code	Description	
005	0.5 m (1.64 ft)	Standard
010	1.0 m (3.28 ft)	
025	2.5 m (8.20 ft)	
050	5.0 m (16.40 ft)	
001-020	0.1...2.0 m (0.328...6.56 ft) 0.1 m (0.328 ft increments)	Build-to-Order
020-100	2.0...10.0 m (6.56...32.8 ft) 0.5 m (1.64 ft increments)	
100-300	10.0...30.0 m (32.8...98.42 ft) 1.0 m (3.28 ft increments)	

c

Cable Type	
Code	Description
A46	Pre-wired cables for Bulletin 1746-NI16I and -NI16V analog modules.
AA69, AB69, BA69, BB69, BC69, BD69, C69, D69, EA69, EB69, EC69, ED69	Pre-wired cables for Bulletin 1769 analog I/O modules.