



ACCUBEAM™ LAMPS use an innovative reflector design that forms the light beam before it reaches the lens. The innovative corrugated reflector allows for greater light concentration at the centre of the beam giving a light output that is comparable to conventional halogen using less wattage.

ACCUBEAM was designed to deliver a smooth, precise beam pattern and allows for even light distribution; without hot spots or striations.



Order code	Description	Watts (W)	Base	Volts (V)	Beam angle (°)	Beam spread	CBCP (cd)	Average life (hrs)	Initial lumens (lm)	Case qty
PAR20										
MOL : 3 1/2 in. (83 mm) Dia. : 2.5 in. (63.5 mm)										
150001	H50PAR20/NFL/5M/130V/STD ACC	50	E26	130	30	Narrow Flood	1 500	5 000	450	15
PAR30										
MOL : 3 3/4 in. (92 mm) Dia. : 3 1/4 in. (95 mm)										
150008	H50PAR30/NFL/2.5M/120V/STD ACC	50	E26	120	30	Narrow Flood	1 850	2 500	600	15
150009	H50PAR30/NSP/5M/130V/STD ACC	50	E26	130	10	Narrow Spot	6 000	5 000	450	15
150007	H50PAR30/NFL/5M/130V/STD ACC	50	E26	130	30	Narrow Flood	1 850	5 000	450	15
150014	H75PAR30/NFL/2.5M/120V/STD ACC	75	E26	120	30	Narrow Flood	3 200	2 500	1 100	15
150015	H75PAR30/NSP/5M/130V/STD ACC	75	E26	130	10	Narrow Spot	9 000	5 000	825	15
150013	H75PAR30/NFL/5M/130V/STD ACC	75	E26	130	30	Narrow Flood	3 200	5 000	825	15
150011	H75PAR30/FL/5M/130V/STD ACC	75	E26	130	40	Flood	1 600	5 000	825	15
PAR38										
MOL : 5 1/16 in. (135 mm) Dia. : 4 3/4 in. (121 mm)										
150066	H45PAR38/SP/5M/130V/STD ACC	45	E26SKT	130	10	Spot	7 000	5 000	390	15
150041	H45PAR38/FL/5M/130V/STD ACC	45	E26SKT	130	30	Flood	1 700	5 000	390	15
150101	H75PAR38/FL/5M/130V/STD ACC	75	E26SKT	130	30	Flood	3 300	5 000	825	15

¹This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.



ACCUBEAM™ Lamps