

Product datasheet
Characteristics

MA8IMA12

Surge mod IMA - 120kA - 600Y/347VAC - 3P3W - T2 - CSA



Main

Product or component type	Surge protection module
Range of product	Surgelogic
Device short name	IMA
Accessory / separate part category	Replacement part

Complementary

Surge current	120 kA per phase
[Ue] rated operational voltage	600Y/347 V AC
Network number of phases	3 phases
Wiring configuration	3-wire
Connections - terminals	Terminals
[Uc] maximum continuous operating voltage	420 V
Nominal discharge current	20 kA
Short-circuit protection	200 kA
Local signalling	Status LED, green = normal operation
Provided equipment	Alarm enable/disable switch
Mounting support	Panel mounting
Height	158.8 mm
Width	82.8 mm
Depth	68.3 mm

Environment

NEMA degree of protection	NEMA 2
enclosure material	Plastic, colour : black
standards	ANSI/IEEE C62.41 ANSI/IEEE C62.45 NEC 285 CSA C22.2 No 8 1986 UL 1283 ed. 5 UL 1449 ed. 4
ambient air temperature for operation	65 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 4Q2016 Will be Compliant on 4Q2016

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.