


# LUTZE TOP-T Fittings PG

## Metal PG



### Characteristics

- Integrated strain relief
- Anti-twist design
- Wide sealing and clamping range
- Easy to install
- Temperature range  
-20°C - +100°C  
-4°F - +212°F
- Protection class  
IP68

### Fitting Specifications

Connecting thread	PG as per DIN 40430
Material	Brass, nickel plated
Clamping insert	Polyamide 6
Seal	CR Chloroprene
O-ring	Rubber NBR

### Item Specific Approvals

- UL Recognized (R) or UL Listed (L), as per table
- Type 4X for UL Recognized and UL Listed items

Part No.	Thread	Clamping Range Ø inches	Clamping Range Ø mm	TL mm	SW1 mm	SW2 mm	H mm	UL R / L
<b>PG</b>								
<b>FMPG7</b>	PG 7	0.118-0.256	3-6.5	6	14	14	22	R
<b>FMPG9</b>	PG 9	0.157-0.315	4-8	6	17	17	23.5	
<b>FMPG11</b>	PG 11	0.197-0.394	5-10	6	20	20	26	
<b>FMPG13</b>	PG 13.5	0.236-0.472	6-12	6.5	22	22	24.5	R
<b>FMPG16</b>	PG 16	0.394-0.551	10-14	6.5	24	24	28	
<b>FMPG21</b>	PG 21	0.512-0.709	13-18	7.2	30	30	32.5	L
<b>FMPG29</b>	PG 29	0.709-0.984	18-25	8	40	40	38.5	L
<b>FMPG36</b>	PG 36	0.866-1.260	22-32	9	50	50	48	L
<b>FMPG42</b>	PG 42	1.181-1.496	30-38	12	58	58	48.5	L
<b>FMPG48</b>	PG 48	1.339-1.732	34-44	14	64	64	53	L
<b>LONG THREAD</b>								
<b>FMPG7-L</b>	PG 7	0.118-0.256	3-6.5	10	14	14	22	R
<b>FMPG9-L</b>	PG 9	0.157-0.315	4-8	10	17	17	23.5	
<b>FMPG11-L</b>	PG 11	0.197-0.394	5-10	10	20	20	26	
<b>FMPG13-L</b>	PG 13.5	0.236-0.472	6-12	10	22	22	24.5	R
<b>FMPG16-L</b>	PG 16	0.394-0.551	10-14	10	24	24	28	L
<b>FMPG21-L</b>	PG 21	0.512-0.709	13-18	12	30	30	32.5	L
<b>FMPG29-L</b>	PG 29	0.709-0.984	18-25	12	40	40	38.5	L

Specifications are subject to change without prior notice