

Ordering Information - DP Contactor



Select options in 7 through 11 for Standard Configurations

7	Ampere Rating
B	25A
C	30A
D	40A

8	Number of Poles
2	2 Poles
3	3 Poles
4	4 Poles

9	Contactors Coil Voltage
A	110-120V 60Hz
	110V 50Hz
B	208-240V 60Hz
	220V 50Hz
C	440-480V 60Hz
	380-415V 50Hz
D	575-600V 60Hz
	550V 50Hz
E	12V 50/60 Hz
F	277V 60Hz
H	24V 50/60Hz

10	Line Terminal
A	Binding Screw w/QC
B	Lug w/ Slotted Screw w/QC
C	Binding Screw
D	Lug with Slotted Screw
L	Sems Clamp w/QC ¹
M	Sems Clamp ¹
N	Lug w/ Hex Head Screw
P	Lug w/ Hex Head Screw w/QC

11	Load Terminal ²
A	Binding Screw w/QC
B	Lug w/ Slotted Screw w/QC
C	Binding Screw
D	Lug with Slotted Screw
L	Sems Clamp w/QC ¹
M	Sems Clamp ¹
N	Lug w/ Hex Head Screw
P	Lug w/ Hex Head Screw w/QC

¹Not available in 40 FLA

²To mount overload relay on contactor load terminal:
 - Select option "M", Sems Clamp for 25/30amp
 - Select option "D", Lug with Slotted Screw for 40amp

Add Options 12 through 16 for Customized Configurations

12	Auxiliary Contacts	Left	Right	Front
A	-	-	-	-
B	250 V	1 SPDT	-	-
C	250 V	-	1 SPDT	-
D	250 V	2 SPDT	-	-
E	250 V	-	2 SPDT	-
F	250 V	1 SPDT	1 SPDT	-
G	250 V	2 SPDT	2 SPDT	-
H	600 V	1 NO-NC	-	-
J	600 V	-	1 NO-NC	-
K	600 V	1 NO-NC	1 NO-NC	-
L	600 V	2 NO	-	-
M	600 V	-	2 NO	-
N	600 V	2 NO	2 NO	-
P	600 V	1 NO-NC	2 NO	-
Q	600 V	2 NO	1 NO-NC	-
R	600 V	-	-	1 NO
S	600 V	-	-	1 NC
T	600 V	-	-	1 NO-NC

13	Modification
0	None
1	Coil Rotated with Coil Terminals Down
3	DIN Rail Mounting Provision
4	Coil Rotated with Coil Terminals Down and DIN Rail Mounting Provision
5	Dummy Quick Connect Tabs on Coil
6	Coil Rotated with Coil Terminals Down and Dummy Quick Connect Tabs on Coil
8	Dummy Quick Connect Tabs on Coil and DIN Rail Mounting Provision
9	Coil Rotated with Coil Terminals Down and DIN Rail Mounting Provision and Dummy Quick Connect Tabs on Coil

14	Terminal Marking
A	Standard Terminal Marking
B	Inverse Terminal Marking
C	Reverse Terminal Marking
D	Without Terminal Marking

15	Special Marking
A	None
*	Customer Specific options assigned by Factory

16	Packaging
A	Single Pack
P	Bulk Pack - Minimum order quantity 96 pieces with multiples of 8 pieces

Ordering Bulk Packs? Just add A0AAP to the Standard Product Number.

Complete Product Numbers:

11 digits for Standard

16 digits for Customized

Omit digit 12 through 16, if the selection is "A0AAA"