



## Main

Range of product	Homeline
Product or component type	Load Center
Line Rated Current	125 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Wall mount
Short-circuit current	22 kA

## Complementary

Electrical connection	Lugs
AWG gauge	AWG 4...250 kcmil aluminium/copper
Load center type	Main breaker
Number of spaces	60
Number of circuits	120
Number of tandem circuit breakers	60
Phase	1 phase
Cover type	Combination flush/surface cover
Device composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Cover colour	White
Box number	24

## Environment

Product certifications	CSA
NEMA degree of protection	NEMA 1 (indoor)
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)

## Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.