



### Main

Range of product	Homeline
Product or component type	Load Centre
[In] rated current	125 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Wall mount
Short-circuit current	10 kA

### Complementary

Electrical connection	Lugs
AWG gauge	AWG 6...AWG 2/0 (aluminium/copper)
Load center type	Main lugs
Number of spaces	8
Number of circuits	16
Number of tandem circuit breakers	8
Network number of phases	1 phase
Cover type	Combination flush/surface cover
Device composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Cover plate colour tint	White
Box number	6

### Environment

product certifications	CSA
NEMA degree of protection	NEMA 1 (indoor)

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1248 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.