

**Product datasheet**  
Characteristics

**JJA36150**  
MOLDED CASE CIRCUIT BREAKER 600V 150A



**Main**

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	J

**Complementary**

[In] rated current	150 A
Number of poles	3
Poles description	3P
Breaking capacity	20 kA 250 V DC 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
[Ue] rated operational voltage	250 V DC 600 V AC
Continuous current rating	80 %
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 4...AWG 4/0 aluminium/copper
Phase connection	ABC
Magnetic hold current	750 A
Magnetic tripping current	1500 A
Height	11.48 in
Width	4.48 in
Depth	5.87 in

**Environment**

product certifications	CCC CE CSA IEC UL listed
ambient air temperature for operation	40 °C

**Offer Sustainability**

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.