

Product availability: Stock - Normally stocked in distribution facility



Main

Product	Load Center Enclosure
Marketing Trade Name	QO

Complementary

Load Center Type	Main breaker
Number of spaces	2
Short Circuit Current Rating	65 kA
Maximum Number of Single Pole Circuits	2
Maximum Number of Tandem Breakers	4
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 14...AWG 4 aluminium/copper
Electrical Connection	Lugs
Grounding Bar	Grounding bar (factory installed)
Electrical connection	Lugs
Wiring configuration	3-wire
Box number	1NM
Height	9.65 in (245 mm)
Width	6.40 in (162.5 mm)
Depth	3.74 in (95 mm)
Tightening torque	3.95 N.M (35 lbf.in) 0.00...0.01 in ² (2.08...5.26 mm ²) AWG 14...AWG 10) 3.95 N.M (35 lbf.in) 0.01...0.01 in ² (3.30...5.26 mm ²) AWG 12...AWG10) 4.52 N.M (40 lbf.in) 0.01 in ² (8.36 mm ²) AWG 8...AWG 4) 4.52 N.M (40 lbf.in) AWG 8...AWG 4) 5.08 N.m (45 lbf.in) AWG 3)

Environment

Enclosure Rating	NEMA 3R outdoor
Product certifications	CSA UL listed

Ordering and shipping details

Category	01081 - INTRA-COMPANY COMPONENTS
Discount Schedule	NET
GTIN	00785901294597
Package weight(Lbs)	0.69 kg (1.53 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration