

Product availability: Stock - Normally stocked in distribution facility



### Main

Range of product	125 A Frame EDB-EGB-EJB
Product or component type	Miniature circuit-breaker
Device short name	EDB
Module type	E-Frame
Trip unit rating	1800 A

### Complementary

Line Rated Current	70 A
Maximum operating voltage	480Y/277 V AC
AWG gauge	AWG 12...AWG 2/0 aluminium AWG 14...AWG 2/0 copper
Breaking capacity	18 KA 277 V AC 25 KA 240 V AC 18 KA 480Y/277 V AC 25 KA 120 V AC 25 kA 120/240 V AC
Circuit breaker application	HACR rated
Depth	102.87 mm (4.05 in)
Electrical connection	Lugs aluminium
Height	143.76 mm (5.66 in)
Holding current	630 A
Local signalling	Trip indicator
Mounting mode	Bolt-on
Number of poles	2
Number of spaces	2
Number of spaces required	2
Product destination	NF panelboard
Product weight	1.36 kg (3 lb(US))
Protection type	Overload Short-circuit
Width	49.78 mm (1.96 in)
Trip unit technology	Thermal-magnetic
Breaking capacity code	D
Tightening torque	34.52 Lbf.in (3.9 N.m) 0.00...0.01 in <sup>2</sup> (2.5...6 mm <sup>2</sup> ) AWG 14...AWG 10) 49.56 Lbf.in (5.6 N.m) 0.02...0.11 in <sup>2</sup> (10...70 mm <sup>2</sup> ) AWG 8...AWG 2/0)

### Environment

Product certifications	CULus
Ambient air temperature for operation	104 °F (40 °C)

## Ordering and shipping details

Category	00931 - EDB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	00785901311034
Package weight(Lbs)	1.11 kg (2.45 lb(US))
Returnability	Yes
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------