

# Spring-Clamp Connection Terminal Blocks

## Standard Feed-Through Blocks

	1492-L3				1492-L3T				1492-L3Q			
Dimensions are not intended to be used for manufacturing purposes. <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.												
<b>Specifications</b>	<i>Feed-through terminal block</i>				<i>Feed-through terminal block with 3 connection points, 2 on one side</i>				<i>Feed-through terminal block with 2 points on each side</i>			
<b>Certifications</b>		<b>CSA</b>	<b>IEC</b>	<b>ATEX</b>		<b>CSA</b>	<b>IEC</b>	<b>ATEX</b>		<b>CSA</b>	<b>IEC</b>	<b>ATEX</b>
<b>Voltage Rating</b>	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
<b>Maximum Current</b>	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A
<b>Wire Range (Rated Cross Section)</b>	#30... 12 AWG	#26... 12 AWG	2.5 mm <sup>2</sup>	2.5 mm <sup>2</sup> (20...12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm <sup>2</sup>	2.5 mm <sup>2</sup> (20...12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm <sup>2</sup>	2.5 mm <sup>2</sup> (20...12 AWG)
<b>Wire Strip Length</b>	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)			
<b>Density</b>	59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)			
<b>Housing Temperature Range</b>	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
<b>Short-Circuit Current Rating (SCCR)</b>	See page 12-78											
<b>Terminal Blocks</b>	<b>Cat. No.</b>		<b>Pkg Qty.</b>		<b>Cat. No.</b>		<b>Pkg Qty.</b>		<b>Cat. No.</b>		<b>Pkg Qty.</b>	
<b>Color</b>	Grey		100		1492-L3T		100		1492-L3Q		100	
	Red		100		1492-L3T-RE		100		1492-L3Q-RE		100	
	Blue		100		1492-L3T-B		100		1492-L3Q-B		100	
	Black		100		1492-L3T-BL		100		1492-L3Q-BL		100	
	Green		100		1492-L3T-G		100		1492-L3Q-G		100	
	Yellow		100		1492-L3T-Y		100		1492-L3Q-Y		100	
	Orange		100		1492-L3T-OR		100		1492-L3Q-OR		100	
	Brown		100		1492-L3T-BR		100		1492-L3Q-BR		100	
	White		100		1492-L3T-W		100		1492-L3Q-W		100	
<b>Accessories</b>	<b>Cat. No.</b>		<b>Pkg Qty.</b>		<b>Cat. No.</b>		<b>Pkg Qty.</b>		<b>Cat. No.</b>		<b>Pkg Qty.</b>	
<b>Mounting Rails</b>	199-DR1		10		199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Steel)	1492-DR5		10		1492-DR5		10		1492-DR5		10	
1 m Symmetrical DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR7		2		1492-DR7		2		1492-DR7		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-EBL3		50		1492-EBL3T		50		1492-EBL3Q		50	
<b>End Barriers</b>	1492-EBL3-B		50		1492-EBL3T-B		50		1492-EBL3Q-B		50	
Grey	1492-EBL3-Y		50		1492-EBL3T-Y		50		1492-EBL3Q-Y		50	
Blue	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
Yellow	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100	
<b>End Anchors and Retainers</b>	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Screwless End Retainer	1492-CJK5-50		10		1492-CJK5-50		10		1492-CJK5-50		10	
<b>DIN Rail — Normal Duty</b>	1492-CJK5-10		20		1492-CJK5-10		20		1492-CJK5-10		20	
<b>DIN Rail — Heavy Duty</b>	1492-CJK5-9		20		1492-CJK5-9		20		1492-CJK5-9		20	
<b>Jumpers</b>	1492-CJK5-8		20		1492-CJK5-8		20		1492-CJK5-8		20	
Plug-in Center Jumper — 50-Pole	1492-CJK5-7		20		1492-CJK5-7		20		1492-CJK5-7		20	
Plug-in Center Jumper — 10-Pole	1492-CJK5-6		20		1492-CJK5-6		20		1492-CJK5-6		20	
Plug-in Center Jumper — 9-Pole	1492-CJK5-5		20		1492-CJK5-5		20		1492-CJK5-5		20	
Plug-in Center Jumper — 8-Pole	1492-CJK5-4		60		1492-CJK5-4		60		1492-CJK5-4		60	
Plug-in Center Jumper — 7-Pole	1492-CJK5-3		60		1492-CJK5-3		60		1492-CJK5-3		60	
Plug-in Center Jumper — 6-Pole	1492-CJK5-2		60		1492-CJK5-2		60		1492-CJK5-2		60	
Plug-in Center Jumper — 5-Pole	1492-PSL3-2		100		1492-PSL3-2		100		1492-PSL3-2		100	
Plug-in Center Jumper — 4-Pole	1492-PSL3-5		100		1492-PSL3-5		100		1492-PSL3-5		100	
Plug-in Center Jumper — 3-Pole	1492-PSL3-10		100		1492-PSL3-10		100		1492-PSL3-10		100	
Plug-in Center Jumper — 2-Pole	1492-TP23		20		1492-TP23		20		1492-TP23		20	
<b>Other Accessories</b>	1492-TPL5		25		1492-TPL5		25		1492-TPL5		25	
Reducing Sleeves #30...#24 AWG (0.13...0.2 mm <sup>2</sup> ) White	1492-EWPL5		20		1492-EWPL5		20		1492-EWPL5		20	
Reducing Sleeves #22...#20 AWG (0.25...0.5 mm <sup>2</sup> ) Grey	1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5	
Reducing Sleeves #18 AWG (0.75...1.0 mm <sup>2</sup> ) Dark Grey	1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5	
Test Plug	1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5	
Test Plug (Stackable)	1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5	
Electrical Warning Plate	1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5	
<b>Marking Systems</b>	1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5	
Snap-In Marker Cards	1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5	
Snap-In Marker Cards	1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5	
Hinged Marker Cards	1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5	
Hinged Marker Cards	1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5	

# Spring-Clamp Connection Terminal Blocks

## Multi-Circuit Feed-Through Blocks





	1492-LD2			1492-LD3				1492-L3QS			
Dimensions are not intended to be used for manufacturing purposes. <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.											
<b>Specifications</b>	<i>Two-circuit feed-through terminal block</i>			<i>Two-circuit feed-through terminal block</i>				<i>Side-by-side two circuit terminal block</i>			
<b>Certifications</b>		<b>CSA</b>	<b>IEC</b>		<b>CSA</b>	<b>IEC</b>	<b>ATEX</b>		<b>CSA</b>	<b>IEC</b>	<b>ATEX</b>
<b>Voltage Rating</b>	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC	25 A	800V AC/DC	550V AC/DC	600V AC/DC	27 A	800V AC/DC	550V AC/DC
<b>Maximum Current</b>	10 A		17.5 A	20 A	25 A	24 A	20 A	25 A	27 A	24 A	21 A
<b>Wire Range (Rated Cross Section)</b>	#28... 16 AWG		1.5 mm <sup>2</sup>	#30... 12 AWG		2.5 mm <sup>2</sup>	0.5...2.5 mm <sup>2</sup> (#20...14 AWG)	#26... 12 AWG		2.5 mm <sup>2</sup>	2.5 mm <sup>2</sup> (20... 12 AWG)
<b>Wire Strip Length</b>	0.39 in. (10 mm)			0.39 in. (10 mm)				0.39 in. (10 mm)			
<b>Density</b>	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)			
<b>Housing Temperature Range</b>	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
<b>Terminal Blocks</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>			
<b>Color</b>	Grey	<b>1492-LD2</b>	50	<b>1492-LD3</b>	25	<b>1492-L3QS</b>	50				
	Red	1492-LD2-RE	50	1492-LD3-RE	25	1492-L3QS-RE	50				
	Blue	<b>1492-LD2-B</b>	50	<b>1492-LD3-B</b>	25	1492-L3QS-B	50				
	Black	1492-LD2-BL	50	1492-LD3-BL	25	1492-L3QS-BL	50				
	Green	1492-LD2-G	50	1492-LD3-G	25	1492-L3QS-G	50				
	Yellow	1492-LD2-Y	50	1492-LD3-Y	25	1492-L3QS-Y	50				
	Orange	1492-LD2-OR	50	1492-LD3-OR	25	1492-L3QS-OR	50				
	Brown	1492-LD2-BR	50	1492-LD3-BR	25	1492-L3QS-BR	50				
	White	1492-LD2-W	50	1492-LD3-W	25	1492-L3QS-W	50				
<b>Accessories</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>			
<b>Mounting Rails</b>											
1 m Symmetrical DIN (Steel)	<b>199-DR1</b>	10	<b>199-DR1</b>	10	<b>199-DR1</b>	10	<b>199-DR1</b>	10			
1 m Symmetrical DIN (Aluminum)	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10			
1 m Hi-Rise Symmetrical DIN (Aluminum)	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2			
1 m Angled Hi-Rise Sym. DIN (Steel)	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2			
<b>End Barriers</b>	Grey	<b>1492-EBLD2</b>	50	<b>1492-EBLD3</b>	20	<b>1492-EBL3Q</b>	50				
	Blue	1492-EBLD2-B	20	1492-EBLD3-B	20	<b>1492-EBL3Q-B</b>	50				
	Yellow	1492-EBLD2-Y	20	<b>1492-EBLD3-Y</b>	20	<b>1492-EBL3Q-Y</b>	50				
<b>End Anchors and Retainers</b>											
Screwless End Retainer	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20			
DIN Rail — Normal Duty	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100			
DIN Rail — Heavy Duty	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50			
<b>Jumpers</b>											
Plug-in Center Jumper — 50-Pole	—	—	<b>1492-CJK5-50</b>	10	—	—	—	—			
Plug-in Center Jumper — 10-Pole	<b>1492-CJL4-10</b>	20	<b>1492-CJK5-10</b>	20	—	—	—	—			
Plug-in Center Jumper — 9-Pole	—	—	<b>1492-CJK5-9</b>	20	—	—	—	—			
Plug-in Center Jumper — 8-Pole	—	—	<b>1492-CJK5-8</b>	20	—	—	—	—			
Plug-in Center Jumper — 7-Pole	—	—	<b>1492-CJK5-7</b>	20	—	—	—	—			
Plug-in Center Jumper — 6-Pole	—	—	<b>1492-CJK5-6</b>	20	—	—	—	—			
Plug-in Center Jumper — 5-Pole	<b>1492-CJL4-5</b>	60	<b>1492-CJK5-5</b>	20	—	—	—	—			
Plug-in Center Jumper — 4-Pole	<b>1492-CJL4-4</b>	60	<b>1492-CJK5-4</b>	60	—	—	—	—			
Plug-in Center Jumper — 3-Pole	<b>1492-CJL4-3</b>	60	<b>1492-CJK5-3</b>	60	—	—	—	—			
Plug-in Center Jumper — 2-Pole	<b>1492-CJL4-2</b>	60	<b>1492-CJK5-2</b>	60	—	—	—	—			
<b>Other Accessories</b>											
Reducing Sleeves #28...24 AWG (0.13...0.2 mm <sup>2</sup> )	1492-PSL2-2	100	1492-PSLS2-2	100	1492-PSL3-2	100	1492-PSL3-2	100			
Reducing Sleeves #22...20 AWG (0.25...0.5 mm <sup>2</sup> )	1492-PSL2-5	100	1492-PSLS2-5	100	1492-PSL3-5	100	1492-PSL3-5	100			
Reducing Sleeves #18 AWG (0.75...1.0 mm <sup>2</sup> )	—	—	—	—	1492-PSL3-10	100	1492-PSL3-10	100			
<b>Test Plug</b>	<b>1492-TPL4</b>	25	—	—	<b>1492-TP23</b>	20	<b>1492-TP23</b>	20			
					<b>1492-TPL5</b>	25	<b>1492-TPL5</b>	25			
<b>Electrical Warning Plate</b>	1492-EWPL4	20	—	—	<b>1492-EWPL5</b>	20	<b>1492-EWPL5</b>	20			
<b>Marking Systems</b>											
Snap-In Marker Cards	<b>1492-M3X12</b> (120/card)*	5	<b>1492-M5X10</b> (144/card)	5	<b>1492-M5X10</b> (144/card)	5	<b>1492-M5X10</b> (144/card)	5			
	<b>1492-M3X5</b> (100/card)	5	<b>1492-M5X5</b> (200/card)	5	<b>1492-M5X5</b> (200/card)	5	<b>1492-M5X5</b> (200/card)	5			
<b>Hinged Marker Cards</b>	—	—	—	—	<b>1492-MH5X10</b> (96/card)	5	<b>1492-MH5X10</b> (96/card)	5			

\* May only be mounted in terminal block corner marking positions.



# Spring-Clamp Connection Terminal Blocks

## Multi-Circuit Feed-Through Blocks

	1492-LD4			1492-LTF3		
Dimensions are not intended to be used for manufacturing purposes. <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.						
	<b>Specifications</b>			<b>Specifications</b>		
	Two-circuit feed-through terminal block			Three-circuit feed-through terminal block with multiple cross connection points		
<b>Certifications</b>		<b>CSA</b>	<b>IEC</b>		<b>CSA</b>	<b>IEC</b>
<b>Voltage Rating</b>	600V AC/DC		800V AC/DC	300V AC/DC		500V AC/DC
<b>Maximum Current</b>	25 A	30 A	32 A	15 A	20 A	
<b>Wire Range (Rated Cross Section)</b>	#26...10 AWG		4 mm <sup>2</sup>	#26...12 AWG	2.5 mm <sup>2</sup>	
<b>Wire Strip Length</b>	0.39 in. (10 mm)			0.39 in. (10 mm)		
<b>Density</b>	49 pcs/ft (163 pcs/m)			59 pcs/ft (196 pcs/m)		
<b>Housing Temperature Range</b>	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
<b>Terminal Blocks</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>
<b>Color</b>	Grey	<b>1492-LD4</b>	20		<b>1492-LTF3</b>	25
	Red	1492-LD4-RE	20		—	—
	Blue	<b>1492-LD4-B</b>	20		—	—
	Black	1492-LD4-BL	20		—	—
	Green	1492-LD4-G	20		—	—
	Yellow	<b>1492-LD4-Y</b>	20		—	—
	Orange	<b>1492-LD4-OR</b>	20		—	—
	Brown	1492-LD4-BR	20		—	—
	White	<b>1492-LD4-W</b>	20		—	—
<b>Accessories</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>
<b>Mounting Rails</b>						
1 m Symmetrical DIN (Steel)		<b>199-DR1</b>	10		<b>199-DR1</b>	10
1 m Symmetrical DIN (Aluminum)		<b>1492-DR5</b>	10		<b>1492-DR5</b>	10
1 m Hi-Rise Sym. DIN (Aluminum)		<b>1492-DR6</b>	2		<b>1492-DR6</b>	2
1 m Angled Hi-Rise Sym. DIN (Steel)		<b>1492-DR7</b>	2		<b>1492-DR7</b>	2
<b>End Barriers</b>	Grey	<b>1492-EBLD4</b>	20		<b>1492-EBLTF3</b>	20
	Blue	<b>1492-EBLD4-B</b>	20		—	—
	Yellow	1492-EBLD4-Y	20		—	—
<b>End Anchors and Retainers</b>						
Screwless End Retainer		<b>1492-ERL35</b>	20		<b>1492-ERL35</b>	20
DIN Rail — Normal Duty		<b>1492-EAJ35</b>	100		<b>1492-EAJ35</b>	100
DIN Rail — Heavy Duty		<b>1492-EAHJ35</b>	50		<b>1492-EAHJ35</b>	50
<b>Jumpers</b>						
Plug-in Center Jumper — 50-Pole		—	—		<b>1492-CJK5-50</b>	10
Plug-in Center Jumper — 10-Pole		<b>1492-CJK6-10</b>	20		<b>1492-CJK5-10</b>	20
Plug-in Center Jumper — 9-Pole		1492-CJK6-9	20		<b>1492-CJK5-9</b>	20
Plug-in Center Jumper — 8-Pole		<b>1492-CJK6-8</b>	20		<b>1492-CJK5-8</b>	20
Plug-in Center Jumper — 7-Pole		1492-CJK6-7	20		<b>1492-CJK5-7</b>	20
Plug-in Center Jumper — 6-Pole		<b>1492-CJK6-6</b>	20		<b>1492-CJK5-6</b>	20
Plug-in Center Jumper — 5-Pole		<b>1492-CJK6-5</b>	20		<b>1492-CJK5-5</b>	20
Plug-in Center Jumper — 4-Pole		<b>1492-CJK6-4</b>	60		<b>1492-CJK5-4</b>	60
Plug-in Center Jumper — 3-Pole		<b>1492-CJK6-3</b>	60		<b>1492-CJK5-3</b>	60
Plug-in Center Jumper — 2-Pole		<b>1492-CJK6-2</b>	60		<b>1492-CJK5-2</b>	60
<b>Vertical Cross Connector*</b>		—	—		<b>1492-CJL5D</b>	20
<b>Other Accessories</b>						
Reducing Sleeves 26...24 AWG (0.13...0.2 mm <sup>2</sup> )		—	—		1492-PSLTF3-2	100
Reducing Sleeves 22...20 AWG (0.25...0.5 mm <sup>2</sup> )		—	—		1492-PSLTF3-5	100
Test Plug		<b>1492-TP23</b>	20		—	—
Electrical Warning Plate		1492-EWPL6	20		—	—
<b>Marking Systems</b>						
Snap-In Marker Cards		<b>1492-M6X10</b> (120/card)	5		<b>1492-SM5X10</b> (144/card)	5
Snap-In Marker Cards		<b>1492-M6X5</b> (200/card)	5		<b>1492-M5X5</b> (200/card)	5

\* Used to electrically connect 2 levels of 1492-LTF3

# Spring-Clamp Connection Terminal Blocks

## Specialty Feed-Through Blocks




	1492-LD2C			1492-LD3C				1492-LD4C		
Dimensions are not intended to be used for manufacturing purposes. <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.										
<b>Specifications</b>	Two-level feed-through terminal block with commoning bar			Two-level feed-through terminal block with commoning bar				Two-level feed-through terminal block with commoning bar		
<b>Certifications</b>		<b>CSA</b>	<b>IEC</b>		<b>CSA</b>	<b>IEC</b>	<b>ATEX</b>		<b>CSA</b>	<b>IEC</b>
<b>Voltage Rating</b>	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC
<b>Maximum Current</b>	10 A		17.5 A	20 A	25 A	24 A	22 A	25 A	30 A	32 A
<b>Wire Range (Rated Cross Section)</b>	#28...16 AWG		1.5 mm <sup>2</sup>	#30...12 AWG		2.5 mm <sup>2</sup>	0.5...2.5 mm <sup>2</sup> (#20...14 AWG)	#26...10 AWG		4 mm <sup>2</sup>
<b>Wire Strip Length</b>	0.39 in. (10 mm)			0.39 in. (10 mm)				0.39 in. (10 mm)		
<b>Density</b>	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)		
<b>Housing Temperature Range</b>	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
<b>Terminal Blocks</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>
<b>Color:</b> Grey	<b>1492-LD2C</b>	50	<b>1492-LD3C</b>	25	<b>1492-LD4C</b>	25				
<b>Accessories</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>
<b>Mounting Rails:</b>										
1 m Symmetrical DIN (Steel)	<b>199-DR1</b>	10	<b>199-DR1</b>	10	<b>199-DR1</b>	10				
1 m Symmetrical DIN (Aluminum)	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10				
1 m Hi-Rise Sym. DIN (Aluminum)	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2				
1 m Angled Hi-Rise Sym. DIN (Steel)	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2				
<b>End Barriers</b> Grey	<b>1492-EBLD2</b>	50	<b>1492-EBLD3</b>	20	<b>1492-EBLD4</b>	20				
<b>End Anchors and Retainers</b>										
Screwless End Retainer	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20				
DIN Rail — Normal Duty	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100				
DIN Rail — Heavy Duty	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50				
<b>Jumpers:</b>										
Plug-in Center Jumper — 50-Pole	—	—	<b>1492-CJK5-50</b>	10	—	—				
Plug-in Center Jumper — 10-Pole	<b>1492-CJL4-10</b>	20	<b>1492-CJK5-10</b>	20	<b>1492-CJK6-10</b>	20				
Plug-in Center Jumper — 9-Pole	—	—	<b>1492-CJK5-9</b>	20	<b>1492-CJK6-9</b>	20				
Plug-in Center Jumper — 8-Pole	—	—	<b>1492-CJK5-8</b>	20	<b>1492-CJK6-8</b>	20				
Plug-in Center Jumper — 7-Pole	—	—	<b>1492-CJK5-7</b>	20	<b>1492-CJK6-7</b>	20				
Plug-in Center Jumper — 6-Pole	—	—	<b>1492-CJK5-6</b>	20	<b>1492-CJK6-6</b>	20				
Plug-in Center Jumper — 5-Pole	<b>1492-CJL4-5</b>	60	<b>1492-CJK5-5</b>	20	<b>1492-CJK6-5</b>	20				
Plug-in Center Jumper — 4-Pole	<b>1492-CJL4-4</b>	60	<b>1492-CJK5-4</b>	60	<b>1492-CJK6-4</b>	60				
Plug-in Center Jumper — 3-Pole	<b>1492-CJL4-3</b>	60	<b>1492-CJK5-3</b>	60	<b>1492-CJK6-3</b>	60				
Plug-in Center Jumper — 2-Pole	<b>1492-CJL4-2</b>	60	<b>1492-CJK5-2</b>	60	<b>1492-CJK6-2</b>	60				
<b>Other Accessories:</b>										
Reducing Sleeves 28...24 AWG (0.13...0.2 mm <sup>2</sup> ) White	1492-PSL2-2	100	1492-PSLS2-2	100	—	—				
Reducing Sleeves 22...20 AWG (0.13...0.2 mm <sup>2</sup> ) Grey	1492-PSL2-5	100	1492-PSLS2-5	100	—	—				
<b>Test Plug</b>	<b>1492-TPL4</b>	25	—	—	<b>1492-TP23</b>	20				
<b>Electrical Warning Plate</b>	1492-EWPL4	20	—	—	1492-EWPL6	20				
<b>Marking Systems:</b>										
Snap-In Marker Cards	<b>1492-M3X12</b> (120/card)*	5	<b>1492-M5X10</b> (144/card)	5	<b>1492-M6X10</b> (120/card)	5				
Snap-In Marker Cards	<b>1492-M3X5</b> (100/card)	5	<b>1492-M5X5</b> (200/card)	5	<b>1492-M6X5</b> (200/card)	5				

\* May only be mounted in terminal block corner marking positions.



## Spring-Clamp Connection Terminal Blocks

Sensor Blocks — 3-Wire

	1492-LS2-3* 1492-LS2-3L*		1492-LSG2-3*		1492-LS2-BR 1492-LS2-B 1492-LSG2	
Dimensions are not intended to be used for manufacturing purposes. <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.						
<b>Specifications</b>	3 conductor sensor block base for plug in distribution blocks		3 conductor sensor ground block base for plug in distribution blocks		Plug in Distribution blocks — internally jumpered	
<b>Certifications</b>		<b>CSA</b>	<b>IEC</b>		<b>CSA</b>	<b>IEC</b>
<b>Voltage Rating (without LED)</b>	300V AC/DC		300V AC/DC		300V AC/DC	
<b>Voltage Rating (with LED)</b>	5...30V AC/DC		—		5...30V AC/DC	
<b>Maximum Current</b>	10 A		10 A		10 A	
<b>Wire Range (Rated Cross Section)</b>	#26...14 AWG		#26...14 AWG		#26...14 AWG	
<b>Wire Strip Length</b>	0.31 in. (8 mm)		0.31 in. (8 mm)		0.31 in. (8 mm)	
<b>Density</b>	59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)	
<b>Housing Temperature Range</b>	-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)	
<b>Terminal Blocks</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>
<b>Color:</b> Grey (Without LED)	<b>1492-LS2-3</b>	50	—	—	—	—
Grey (With LED)	<b>1492-LS2-3L</b>	50	—	—	—	—
Green/Yellow	—	—	1492-LSG2-3	20	<b>1492-LSG2</b>	100
Brown	—	—	—	—	<b>1492-LS2-BR</b>	100
Blue	—	—	—	—	<b>1492-LS2-B</b>	100
<b>Accessories</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>
<b>Mounting Rails:</b>						
1 m Symmetrical DIN (Steel)	<b>199-DR1</b>	10	<b>199-DR1</b>	10	—	—
1 m Symmetrical DIN (Aluminum)	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10	—	—
1 m Hi-Rise Sym. DIN (Aluminum)	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2	—	—
1 m Angled Hi-Rise Sym. DIN (Steel)	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2	—	—
<b>End Barriers</b> Grey	<b>1492-EBLS2-3</b>	50	<b>1492-EBLS2-3</b>	50	Not required	—
<b>End Anchors and Retainers</b>						
Screwless End Retainer	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20	—	—
DIN Rail — Normal Duty	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100	—	—
DIN Rail — Heavy Duty	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50	—	—
<b>Jumpers:</b>						
Plug-in Center Jumper — 50-Pole	<b>1492-CJK5-50</b>	10	—	—	—	—
Plug-in Center Jumper — 10-Pole	<b>1492-CJK5-10</b>	20	—	—	—	—
Plug-in Center Jumper — 9-Pole	<b>1492-CJK5-9</b>	20	—	—	—	—
Plug-in Center Jumper — 8-Pole	<b>1492-CJK5-8</b>	20	—	—	—	—
Plug-in Center Jumper — 7-Pole	<b>1492-CJK5-7</b>	20	—	—	—	—
Plug-in Center Jumper — 6-Pole	<b>1492-CJK5-6</b>	20	—	—	—	—
Plug-in Center Jumper — 5-Pole	<b>1492-CJK5-5</b>	20	—	—	—	—
Plug-in Center Jumper — 4-Pole	<b>1492-CJK5-4</b>	60	—	—	—	—
Plug-in Center Jumper — 3-Pole	<b>1492-CJK5-3</b>	60	—	—	—	—
Plug-in Center Jumper — 2-Pole	<b>1492-CJK5-2</b>	60	—	—	—	—
<b>Other Accessories:</b>						
Reducing Sleeves 28...24 AWG (0.13...0.2 mm <sup>2</sup> ) White	1492-PSLS2-2	100	—	—	1492-PSLS2-2	100
Reducing Sleeves 22...20 AWG (0.25...0.5 mm <sup>2</sup> ) Grey	1492-PSLS2-5	100	—	—	1492-PSLS2-5	100
<b>Marking Systems:</b>						
Snap-In Marker Cards	<b>1492-M5X5</b> (200/card)	5	<b>1492-M5X5</b> (200/card)	5	—	—

\* A combination of two distribution blocks must be used with each base block.



# Spring-Clamp Connection Terminal Blocks




## Sensor Blocks — 4-Wire

**1492-LS2-4\***  
**1492-LS2-4L\***

**1492-LSG2-4\***

**1492-LS2-BR**  
**1492-LS2-B**  
**1492-LSG2**

Dimensions are not intended to be used for manufacturing purposes.  
**Note:** Height dimension is measured from top of rail to top of terminal block.



Specifications	4 conductor sensor block base for plug in distribution blocks			4 conductor sensor ground block base for plug in distribution blocks			Plug In Distribution blocks — internally jumpered		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating (without LED)	300V AC/DC		250V AC/DC	300V AC/DC		250V AC/DC	300V AC/DC		250V AC/DC
Voltage Rating (with LED)	5...30V AC/DC			—			5...30V AC/DC		
Maximum Current	10 A		17.5 A	10 A		17.5 A	10 A		17.5 A
Wire Range (Rated Cross Section)	#26...14 AWG		1.5 mm <sup>2</sup>	#26...14 AWG		1.5 mm <sup>2</sup>	#26...14 AWG		1.5 mm <sup>2</sup>
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.28 in. (7 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	
Color: Grey (Without LED)	<b>1492-LS2-4</b>	50	—	—	—	—	—	—	
Grey (With LED)	1492-LS2-4L	50	—	—	—	—	—	—	
Green/Yellow	—	—	<b>1492-LSG2-4</b>	20	<b>1492-LSG2</b>	100	—	—	
Brown	—	—	—	—	<b>1492-LS2-BR</b>	100	—	—	
Blue	—	—	—	—	<b>1492-LS2-B</b>	100	—	—	
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	<b>199-DR1</b>	10	<b>199-DR1</b>	10	—	—	—	—	
1 m Symmetrical DIN (Aluminum)	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10	—	—	—	—	
1 m Hi-Rise Sym. DIN (Aluminum)	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2	—	—	—	—	
1 m Angled Hi-Rise Sym. DIN (Steel)	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2	—	—	—	—	
End Barriers Grey	<b>1492-EBLS2-4</b>	50	<b>1492-EBLS2-4</b>	50	Not required	—	—	—	
End Anchors and Retainers									
Screwless End Retainer	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20	—	—	—	—	
DIN Rail — Normal Duty	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100	—	—	—	—	
DIN Rail — Heavy Duty	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50	—	—	—	—	
Jumpers:									
Plug-in Center Jumper — 50-Pole	<b>1492-CJK5-50</b>	10	—	—	—	—	—	—	
Plug-in Center Jumper — 10-Pole	<b>1492-CJK5-10</b>	20	—	—	—	—	—	—	
Plug-in Center Jumper — 9-Pole	<b>1492-CJK5-9</b>	20	—	—	—	—	—	—	
Plug-in Center Jumper — 8-Pole	<b>1492-CJK5-8</b>	20	—	—	—	—	—	—	
Plug-in Center Jumper — 7-Pole	<b>1492-CJK5-7</b>	20	—	—	—	—	—	—	
Plug-in Center Jumper — 6-Pole	<b>1492-CJK5-6</b>	20	—	—	—	—	—	—	
Plug-in Center Jumper — 5-Pole	<b>1492-CJK5-5</b>	20	—	—	—	—	—	—	
Plug-in Center Jumper — 4-Pole	<b>1492-CJK5-4</b>	60	—	—	—	—	—	—	
Plug-in Center Jumper — 3-Pole	<b>1492-CJK5-3</b>	60	—	—	—	—	—	—	
Plug-in Center Jumper — 2-Pole	<b>1492-CJK5-2</b>	60	—	—	—	—	—	—	
Other Accessories:									
Reducing Sleeves 28...24 AWG (0.13...0.2 mm <sup>2</sup> ) White	1492-PSLS2-2	100	—	—	1492-PSLS2-2	100	—	—	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm <sup>2</sup> ) Grey	1492-PSLS2-5	100	—	—	1492-PSLS2-5	100	—	—	
Marking Systems:									
Snap-In Marker Cards	<b>1492-M5X5</b> (200/card)	5	<b>1492-M5X5</b> (200/card)	5	—	—	—	—	

\* A combination of three distribution blocks must be used with each base block.




## Spring-Clamp Connection Terminal Blocks

## Isolation Blocks

## 1492-LKD3

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



<b>Specifications</b>		<i>Knife disconnect feed-through terminal block</i>		
Certifications		<b>UL</b>	<b>CSA</b>	<b>IEC</b>
Voltage Rating		600V AC/DC		500V AC/DC
Maximum Current		20 A		24 A
Wire Range (Rated Cross Section)		#30...12 AWG		2.5 mm <sup>2</sup>
Wire Strip Length		0.39 in. (10 mm)		
Density		59 pcs/ft (196 pcs/m)		
Housing Temperature Range		-58...+248 °F (-50...+120 °C)		
<b>Terminal Blocks</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>	
Color	Grey	<b>1492-LKD3</b>	25	
<b>Accessories</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>	
Mounting Rails		<b>199-DR1</b>	10	
1 m Symmetrical DIN (Steel)		<b>1492-DR5</b>	10	
1 m Hi-Rise Sym. DIN (Aluminum)		<b>1492-DR6</b>	2	
1 m Angled Hi-Rise Sym. DIN (Steel)		<b>1492-DR7</b>	2	
End Barriers	Grey	<b>1492-EBL3</b>	50	
End Anchors and Retainers		<b>1492-ERL35</b>	20	
Screwless End Retainer		<b>1492-EAJ35</b>	100	
DIN Rail — Normal Duty		<b>1492-EAHJ35</b>	50	
DIN Rail — Heavy Duty		<b>1492-EAHJ35</b>	50	
Jumpers		<b>1492-CJK5-50</b>	10	
Plug-in Center Jumper — 50-Pole		<b>1492-CJK5-10</b>	20	
Plug-in Center Jumper — 10-Pole		<b>1492-CJK5-9</b>	20	
Plug-in Center Jumper — 9-Pole		<b>1492-CJK5-8</b>	20	
Plug-in Center Jumper — 8-Pole		<b>1492-CJK5-7</b>	20	
Plug-in Center Jumper — 7-Pole		<b>1492-CJK5-6</b>	20	
Plug-in Center Jumper — 6-Pole		<b>1492-CJK5-5</b>	20	
Plug-in Center Jumper — 5-Pole		<b>1492-CJK5-4</b>	60	
Plug-in Center Jumper — 4-Pole		<b>1492-CJK5-3</b>	60	
Plug-in Center Jumper — 3-Pole		<b>1492-CJK5-2</b>	60	
Plug-in Center Jumper — 2-Pole		<b>1492-CJK5-2</b>	60	
Other Accessories		<b>1492-PSL3-2</b>	100	
Reducing Sleeves 28...24 AWG (0.13...0.2 mm <sup>2</sup> ) White		<b>1492-PSL3-5</b>	100	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm <sup>2</sup> ) Grey		<b>1492-PSL3-10</b>	100	
Reducing Sleeves 18 AWG (0.75...1.0 mm <sup>2</sup> ) Dark Grey		<b>1492-TP23</b>	20	
Test Plug		<b>1492-TPL5</b>	25	
Test Plug (Stackable)		<b>1492-EWPL5</b>	20	
Electrical Warning Plate		<b>1492-M5X10</b> (144/card)	5	
Marking Systems		<b>1492-M5X5</b> (200/card)	5	
Snap-In Marker Cards			5	
Snap-In Marker Cards			5	

# Spring-Clamp Connection Terminal Blocks

## Plug-In Style Blocks & Analog Loop Control Block

	1492-L3P			1492-LDG3P			1492-LDAG3		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
<b>Specifications</b>	Single circuit plug-in component block for a variety of components			Terminal block with slot for plug-in component, feed-through circuit and 1 ground connection			Analog Loop Control Terminal Block with 2 Feed-Through Circuits and 1 Ground Connection		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC		500V AC/DC	300V AC/DC		250V AC/DC	300V AC/DC		250V AC/DC
Maximum Current	20 A		24 A	10 A		20 A	10 A		24 A
Wire Range (Rated Cross Section)	#30...12 AWG		4 mm <sup>2</sup>	#26...12 AWG		2.5 mm <sup>2</sup>	#26...12 AWG		2.5 mm <sup>2</sup>
Wire Strip Length	0.39 in. (10 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
<b>Terminal Blocks</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>	
Color	Grey	<b>1492-L3P</b>	25	<b>1492-LDG3P</b>	25		<b>1492-LDAG3</b>	25	
<b>Accessories</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>		<b>Cat. No.</b>	<b>Pkg Qty.</b>	
Mounting Rails									
1 m Symmetrical DIN (Steel)	<b>199-DR1</b>	10		<b>199-DR1</b>	10		<b>199-DR1</b>	10	
1 m Symmetrical DIN (Aluminum)	<b>1492-DR5</b>	10		<b>1492-DR5</b>	10		<b>1492-DR5</b>	10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	<b>1492-DR6</b>	2		<b>1492-DR6</b>	2		<b>1492-DR6</b>	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	<b>1492-DR7</b>	2		<b>1492-DR7</b>	2		<b>1492-DR7</b>	2	
End Barrier	<b>1492-EBL3</b>	50		<b>1492-EBLDAG3</b>	20		<b>1492-EBLDAG3</b>	20	
End Anchors and Retainers									
Screwless End Retainer	<b>1492-ERL35</b>	20		<b>1492-ERL35</b>	20		<b>1492-ERL35</b>	20	
DIN Rail — Normal Duty	<b>1492-EAJ35</b>	100		<b>1492-EAJ35</b>	100		<b>1492-EAJ35</b>	100	
DIN Rail — Heavy Duty	<b>1492-EAHJ35</b>	50		<b>1492-EAHJ35</b>	50		<b>1492-EAHJ35</b>	50	
Jumpers									
Plug-In Center Jumper — 50-pole	<b>1492-CJK5-50</b>	10		<b>1492-CJLJ5-50</b>	10		<b>1492-CJLJ5-50</b>	10	
Plug-In Center Jumper — 10-pole	<b>1492-CJK5-10</b>	20		<b>1492-CJLJ5-10</b>	20		<b>1492-CJLJ5-10</b>	20	
Plug-In Center Jumper — 9-pole	<b>1492-CJK5-9</b>	20		1492-CJLJ5-9	20		1492-CJLJ5-9	20	
Plug-In Center Jumper — 8-pole	<b>1492-CJK5-8</b>	20		<b>1492-CJLJ5-8</b>	20		<b>1492-CJLJ5-8</b>	20	
Plug-In Center Jumper — 7-pole	<b>1492-CJK5-7</b>	20		<b>1492-CJLJ5-7</b>	20		<b>1492-CJLJ5-7</b>	20	
Plug-In Center Jumper — 6-pole	<b>1492-CJK5-6</b>	20		<b>1492-CJLJ5-6</b>	20		<b>1492-CJLJ5-6</b>	20	
Plug-In Center Jumper — 5-pole	<b>1492-CJK5-5</b>	20		<b>1492-CJLJ5-5</b>	20		<b>1492-CJLJ5-5</b>	20	
Plug-In Center Jumper — 4-pole	<b>1492-CJK5-4</b>	60		<b>1492-CJLJ5-4</b>	60		<b>1492-CJLJ5-4</b>	60	
Plug-In Center Jumper — 3-pole	<b>1492-CJK5-3</b>	60		<b>1492-CJLJ5-3</b>	60		<b>1492-CJLJ5-3</b>	60	
Plug-In Center Jumper — 2-pole	<b>1492-CJK5-2</b>	60		<b>1492-CJLJ5-2</b>	60		<b>1492-CJLJ5-2</b>	60	
Other Accessories									
Disconnect Plug	<b>1492-DPL</b>	50		<b>1492-DPL</b>	50		—	—	
Component Plug	<b>1492-CPL</b>	50		<b>1492-CPL</b>	50		—	—	
Fuse Plug									
Without Blown Fuse Indicator	<b>1492-FPK2</b>	20		<b>1492-FPK2</b>	20		—	—	
10...36V Blown Fuse Indicator	<b>1492-FPK224</b>	20		* <b>1492-FPK224</b>	20		—	—	
35...70V Blown Fuse Indicator	1492-FPK248	20		* 1492-FPK248	20		—	—	
60...150V Blown Fuse Indicator	<b>1492-FPK2120</b>	20		* <b>1492-FPK2120</b>	20		—	—	
140...250V Blown Fuse Indicator	<b>1492-FPK2250</b>	20		* <b>1492-FPK2250</b>	20		—	—	
Reducing Sleeves 28...24 AWG (0.13...0.2 mm <sup>2</sup> ) White	1492-PSL3-2	100		—	—		—	—	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm <sup>2</sup> ) Grey	1492-PSL3-5	100		—	—		—	—	
Reducing Sleeves 18 AWG (0.75...1.0 mm <sup>2</sup> ) Dark Grey	1492-PSL3-10	100		—	—		—	—	
Test Plug	<b>1492-TPL5</b>	25		<b>1492-TP23</b>	20		—	—	
Electrical Warning Plate	<b>1492-EWPL5</b>	20		—	—		—	—	
Marking Systems									
Snap-In Marker Cards	<b>1492-M5X10</b> (144/card)	5		<b>1492-M5X10</b> (144/card)	5		<b>1492-M5X10</b> (144/card)	5	
Snap-In Marker Cards	<b>1492-M5X5</b> (200/card)	5		<b>1492-M5X5</b> (200/card)	5		<b>1492-M5X5</b> (200/card)	5	

\* When using Cat. No. 1492-LDG3P with a fuse plug, a center jumper cannot be used on the top level. The only jumper option to use in combination with a fuse plug is a 2-pole side jumper: Cat. No. 1492-SJLM5-2.





Screwless Center Jumpers



For Use With	Color	Pkg Qty.	Cat. No.
1492-L2..., L2T, L2Q, LD2, LD2C	Yellow	60	<b>1492-CJL4-2</b>
		60	<b>1492-CJL4-3</b>
		60	<b>1492-CJL4-4</b>
		60	<b>1492-CJL4-5</b>
		20	<b>1492-CJL4-10</b>
1492-LM3, LC3, LDC3, LDAG3, LDG3P, JKD3..., J3P..., J3, J3TW (see Note)	Yellow	60	<b>1492-CJLJ5-2</b>
	Red	60	1492-CJLJ5-2-R
	Blue	60	1492-CJLJ5-2-B
	Black	60	1492-CJLJ5-2-BL
	Yellow	60	<b>1492-CJLJ5-3</b>
	Red	60	1492-CJLJ5-3-R
	Blue	60	1492-CJLJ5-3-B
	Black	60	1492-CJLJ5-3-BL
	Yellow	60	<b>1492-CJLJ5-4</b>
		20	<b>1492-CJLJ5-5</b>
		20	<b>1492-CJLJ5-6</b>
		20	<b>1492-CJLJ5-7</b>
		20	<b>1492-CJLJ5-8</b>
		20	1492-CJLJ5-9
		20	<b>1492-CJLJ5-10</b>
	Red	20	<b>1492-CJLJ5-10-R</b>
	Blue	20	<b>1492-CJLJ5-10-B</b>
	Black	20	<b>1492-CJLJ5-10-BL</b>
	White	20	<b>1492-CJLJ5-10-W</b>
	Yellow	10	<b>1492-CJLJ5-50</b>
Red	10	<b>1492-CJLJ5-50-R</b>	
Blue	10	1492-CJLJ5-50-B	
Black	10	<b>1492-CJLJ5-50-BL</b>	
White	10	<b>1492-CJLJ5-50-W</b>	

For Use With	Pkg Qty.	Cat. No.
1492-RFB4	10	1492-CJR8-2
	10	1492-CJR8-3
	10	1492-CJR8-4
	10	1492-CJR8-5
	10	1492-CJR8-6
	10	1492-CJR8-7
	10	1492-CJR8-8
	10	1492-CJR8-9
	10	<b>1492-CJR8-10</b>
	1492-RAFB4	10
10		1492-CJRA10-3
10		1492-CJRA10-4
10		1492-CJRA10-5

For Use With	Color	Pkg Qty.	Cat. No.
1492-J4, J4M (see Note)	Yellow	60	<b>1492-CJLJ6-2</b>
	Red	60	1492-CJLJ6-2-R
	Blue	60	1492-CJLJ6-2-B
	Black	60	1492-CJLJ6-2-BL
	Yellow	60	<b>1492-CJLJ6-3</b>
	Red	60	1492-CJLJ6-3-R
	Blue	60	1492-CJLJ6-3-B
	Black	60	1492-CJLJ6-3-BL
	Yellow	60	<b>1492-CJLJ6-4</b>
	Yellow	20	<b>1492-CJLJ6-10</b>
	Red	20	<b>1492-CJLJ6-10-R</b>
	Blue	20	<b>1492-CJLJ6-10-B</b>
	Black	20	<b>1492-CJLJ6-10-BL</b>
	Yellow	10	<b>1492-CJLJ6-41</b>
	Red	10	<b>1492-CJLJ6-41-R</b>
Blue	10	1492-CJLJ6-41-B	
Black	10	1492-CJLJ6-41-BL	
1492-L6, L6T, L16D	Yellow	60	<b>1492-CJL8-2</b>
		60	<b>1492-CJL8-3</b>
		60	<b>1492-CJL8-4</b>
		10	<b>1492-CJL8-32</b>
1492-L10	Yellow	25	<b>1492-CJL10-2</b>
1492-L16	Yellow	25	<b>1492-CJL12-2</b>
1492-L35	Yellow	10	<b>1492-CJL16-2</b>
1492-L3, L3T, L3Q, L3P, LD3, LD3C, LKD3, LTF3, LS2..., L16D	Yellow	60	<b>1492-CJK5-2</b>
		60	<b>1492-CJK5-3</b>
		60	<b>1492-CJK5-4</b>
		20	<b>1492-CJK5-5</b>
		20	<b>1492-CJK5-6</b>
		20	<b>1492-CJK5-7</b>
		20	<b>1492-CJK5-8</b>
		20	<b>1492-CJK5-9</b>
		20	<b>1492-CJK5-10</b>
		10	<b>1492-CJK5-50</b>
1492-L4, L4T, L4Q, LD4DF, LD4DR, LD4SS, LD4, LD4C, L16D	Yellow	60	<b>1492-CJK6-2</b>
		60	<b>1492-CJK6-3</b>
		60	<b>1492-CJK6-4</b>
		20	<b>1492-CJK6-5</b>
		20	<b>1492-CJK6-6</b>
		20	1492-CJK6-7
		20	<b>1492-CJK6-8</b>
		20	1492-CJK6-9
		20	<b>1492-CJK6-10</b>
		20	<b>1492-CJK6-20</b>