

CH223NAWK

100A 2P SN Type 12 240VAC/250VDC Heavy Duty
Fusible Safety Switch



Main

Product or component type	Single Throw Safety Switch
Disconnecter device type	Fusible disconnect
Number of poles	2
Electrical connection	Lugs
Series name	Heavy duty

Complementary

[In] rated current	100 A
Device composition	Neutral (factory installed)
Device mounting	Surface
[Ue] rated operational voltage	240 V DC 250 V AC
AWG gauge	AWG 14...AWG 10 (copper) AWG 12...AWG 1/0 (aluminium)

Environment

product certifications	CSA
NEMA degree of protection	NEMA 3R/12 galvanized steel

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.