

Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Lumens at 120 V (lm)	Case qty
B10 Suitable for base up									
MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)									
50624	25B10/F/3M/130V/STD	25	E26	130	Frost	3 000	CC-2V	165	120
50622	40B10/CL/3M/130V/STD	40	E26	130	Clear	3 000	CC-2V	280	120
50625	40B10/F/3M/130V/STD	40	E26	130	Frost	3 000	CC-2V	280	120
¹ 50623	60B10/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-7A/3	415	120
¹ 50626	60B10/F/3M/130V/STD	60	E26	130	Frost	3 000	C-7A/3	415	120
MOL : 3 9/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)									
50544	40B10/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	280	120
50613	40B10/F/3M/E12/130V/STD	40	E12	130	Frost	3 000	CC-2V	280	120
52150	40B10/WH/3M/E12/130V/STD	40	E12	130	White	3 000	C-7A	230	500
50545	60B10/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	C-7A/3	430	120
50614	60B10/F/3M/E12/130V/STD	60	E12	130	Frost	3 000	C-7A/3	430	120
MOL : 3 9/32 in. (101 mm) LCL : 1 25/32 in. (45 mm)									
50549	40B10/CL/3M/E14/130V/STD	40	E14	130	Clear	3 000	CC-2V	280	120
50552	40B10/F/3M/E14/130V/STD	40	E14	130	Frost	3 000	CC-2V	280	120
50550	60B10/CL/3M/E14/130V/STD	60	E14	130	Clear	3 000	C-7A/3	430	120
50553	60B10/F/3M/E14/130V/STD	60	E14	130	Frost	3 000	C-7A/3	430	120
C7									
MOL : 2 1/8 in. (54 mm) LCL : 1 1/2 in. (38 mm)									
50967	4C7/CL/3M/E12/125V/STD	4	E12	125	Clear	3 000	C-7A	25	500
22008	7C7/CL/2M/E12/120V/2P/STD	7	E12	120	Clear	2 000	C-7A	26	120
CA4.5									
MOL : 2 3/4 in. (70 mm) LCL : 1 3/8 in. (41 mm)									
50634	7.5CA4.5/CL/2M/E12/120V/STD	7.5	E12	120	Clear	2 000	C-7A	30	120
50633	7.5CA4.5/CL/2M/E12/130V/STD	7.5	E12	130	Clear	2 000	C-7A	25	500
52154	7.5CA4.5/F/2M/E12/130V/STD	7.5	E12	130	Frost	2 000	C-7A	30	500
52153	10CA4.5/CL/2M/E12/130V/STD	10	E12	130	Clear	2 000	C-7A	40	500
CA8									
MOL : 3 9/32 in. (91 mm) LCL : 1 25/32 in. (45 mm)									
52155	10CA8/CL/2.5M/E12/130V/STD	10	E12	130	Clear	2 500	C-7A	50	500
52157	10CA8/F/2.5M/E12/130V/STD	10	E12	130	Frost	2 500	C-7A	50	500
50641	15CA8/CL/2.5M/E12/130V/STD	15	E12	130	Clear	2 500	C-7A	70	120
10269	15CA8/F/2.5M/E12/130V/STD	15	E12	130	Frost	2 500	C-7A	70	500
52156	25CA8/CL/2.5M/E12/130V/STD	25	E12	130	Clear	2 500	C-7A	120	500
50643	25CA8/F/2.5M/E12/130V/STD	25	E12	130	Frost	2 500	C-7A	115	120
50642	40CA8/CL/2.5M/E12/130V/STD	40	E12	130	Clear	2 500	C-7A	215	500
50644	40CA8/F/2.5M/E12/130V/STD	40	E12	130	Frost	2 500	C-7A	215	500
CA10									
MOL : 3 29/32 in. (99 mm) LCL : 2 1/8 in. (54 mm)									
51051	25CA10/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-7A	120	500
50629	25CA10/F/3M/130V/STD	25	E26	130	Frost	3 000	C-7A	115	500
50627	40CA10/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-7A	215	500
50630	40CA10/F/3M/130V/STD	40	E26	130	Frost	3 000	C-7A	205	500
¹ 50628	60CA10/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-7A	465	500
¹ 50631	60CA10/F/3M/130V/STD	60	E26	130	Frost	3 000	C-7A	470	500
MOL : 4 3/32 in. (104 mm) LCL : 1 7/8 in. (48 mm)									
50615	25CA10/CL/3M/E12/130V/STD	25	E12	130	Clear	3 000	CC-2V	135	120
50618	25CA10/F/3M/E12/130V/STD	25	E12	130	Frost	3 000	CC-2V	115	120
50616	40CA10/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	235	120
50619	40CA10/F/3M/E12/130V/STD	40	E12	130	Frost	3 000	CC-2V	205	120
50617	60CA10/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	CC-2V	455	120
50620	60CA10/F/3M/E12/130V/STD	60	E12	130	Frost	3 000	CC-2V	450	120

¹ This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

General Service Lamps