

Effortless efficiency

ACS580 general purpose drive



Designed to simplify drive selection, set up, operation and maintenance, the ACS580 general purpose drive conquers more applications in more industries without the head scratching complexities. The ACS580's essential built-in features and intuitive user interfaces offers out-of-the-box, effortless efficiency.

Simple. Connected. Local.

Get started, in minutes

- Predefined primary settings menu means quick and easy set up
- A variety of control macros simplifies the electrical aspects of commissioning
- No need to know parameters or use any programming language
- Directly access all drive functions
- Motor defaults are set to match Baldor Super E motors

Get connected, without the hassle

- Optional Bluetooth assistant control panel allows you to control your drive from up to 250 ft and out of the arc flash boundary
- Supports all industrial standard protocols via optional plug-in modules
- USB port allows transfer of information between PC and drive with no additional hardware
- Free DriveComposer software to program and monitor drive performance

Get what you need, wherever you are

- ACS580 drives are made in America and stocked at a channel partner location near you
- ABB's drive services support is available 24/7

Technical data	
Voltage and power range	3-phase, Un 380 to 480 V, +10%/-15% ACS580-01: from 1 to 350 hp
Frequency	50/60 Hz \pm 10%
Motor control types	Scalar and sensorless vector AC induction Permanent magnet SynRM
Compatible motors	UL Type 1 UL Type 12
Enclosures	UL Type 1 UL Type 12
Wall-mount Flange-mount (option)	up to 350 HP*
Ambient temperature	ACS580-01: -15 to 40°C. No frost allowed. R1 to R9 from +40 to +50 °C with derating
Altitude	without derating 0 to 1,000m 1,000 to 4,000m with derating of 1%/100m
Control panel	Advanced (standard) Bluetooth (optional)
Product Compliance	UL 508C; NEMA 250-2008; CE; Low Voltage Directive 2006/95/EC, EN 61800-5-1: 2007 Machinery Directive 2006/42/EC, EN 61800-5-2: 2007 EMC Directive 2004/108/EC, EN 61800-3: 2004 + A1: 2012 RoHS directive 2011/65/EU ACS580-07 (R10-R11) CE Quality assurance system ISO 9001 and Environmental system ISO 14001 Waste electrical and electronic equipment directive (WEEE) 2002/96/EC RoHS directive 2011/65/EU EAC

*350 HP rating at 30°C ambient

There is more to this drive.

The ACS580 is designed to benefit more applications within more industries, while providing more options with more flexibility.


Adaptive Programming now allows you to customize the drive to your application.

Increased power range (up to 350 Hp) available in a compact, wall-mounted product.

UL Type 12 drives have a **reduced footprint** (same as UL Type 1), providing more mounting flexibility in harsh environments.

Enclosures are also smaller than competitor's solutions.

Color coded connection terminals make the installation and wiring process quick and easy.



Applications

Pumps
Fans
Compressors
Conveyors
Blowers
Extruders
Mixers
Centrifuges

Industries

Food and beverage
Material handling
Chemical, oil and gas
Agriculture
Rubber and plastics
Sawmills
Water handling
Automotive



Built to last.

ACS580 drives feature coated boards to provide improved reliability in harsh environments.

Additionally, all ACS580 drives are tested in maximum temperature and with nominal loads. Tests include both performance and all protective functions.



ABB drives are the global benchmark for quality, reliability, and performance.

ABB Inc
Robotics and Motion
Drives and Controls
16250 W. Glendale Drive
New Berlin, WI 53151

abb.com/drives

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB. Copyright© 2017 ABB
All rights reserved

Essential features inside.

Integrated STO, Safe Torque Off*

Satisfies SIL 3, PLe safety level

Embedded Modbus RTU (RS 485)

Fieldbus protocol with removeable terminal for ease of connection

Option slots

I/O extension modules can be installed in option SLOT 2 in the control unit

External +24V AC/DC

Power up the control unit (frames R6-R11) with an external +24V supply

USB interface for PC tool connection

Transfer information between PC and drive with no additional hardware

Patented swinging choke

Harmonic mitigation even on partial loads



How to videos



ACS580 Website

Additional technical information, white papers, case studies and application overviews