



Product availability: Stock - Normally stocked in distribution facility



Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip Unit Type	Thermal-magnetic
Rating Code	A

Complementary

Line Rated Current	225 A
Number of Poles	3P
Interrupt Rating	42 KA 120 V AC 42 KA 240 V AC 30 KA 480Y/277 V AC 22 kA 600 V AC
[Ue] rated operational voltage	600 V AC 250 V DC
Mounting mode	I-Line
Electrical connection	Lugs load I-Line connection line
Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	1125 A
Magnetic tripping current	2250 A
Wiring configuration	3-wire
Height	279.40 mm (11 in)
Width	152.40 mm (6 in)
Depth	148.34 mm (5.84 in)

Environment

Product certifications	UL listed CSA
------------------------	------------------

Ordering and shipping details

Category	01040 - LA/LH BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901241843
Package weight(Lbs)	8.15 kg (17.97 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------