



APC Symmetra LX 4kVA Power Module, 200/208V

Part Number: SYPM4KP



[Technical Specifications](#) [Product Overview](#) [Documentation](#) [Ratings and Reviews](#)

Output

Output Power Capacity	3200 Watts / 4000 VA
Max Configurable Power	3200 Watts / 4000 VA
Nominal Output Voltage	100V, 120V, 200V, 208V
Output Voltage Note	Configurable for 120/208 or 120/240 output voltage
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	47 - 63 Hz
Other Output Voltages	240
Crest Factor	up to 5 : 1
Topology	Double Conversion Online
Waveform Type	Sine wave
Output Connections	(1) Hard Wire 4-wire (2PH + N +G)

Input

Nominal Input Voltage	200V, 208V
Input Frequency	45 - 65 Hz (auto sensing)
Input voltage range for main operations	155 - 276V
Other Input Voltages	240V

Physical

Maximum Height	5.90 inches (150 mm)
----------------	----------------------

Maximum Width	9.84 inches (250 mm)
Maximum Depth	22.23 inches (565 mm)
Net Weight	33.00 lbs. (15.00 kg)
Shipping Weight	40.00 lbs. (18.18 kg)
Shipping Height	17.30 inches (439 mm)
Shipping Width	13.00 inches (330 mm)
Shipping Depth	31.10 inches (790 mm)
Color	Silver
Units per Pallet	6.00

Environmental

Operating Environment	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 feet (0-4500 meters)
Audible noise at 1 meter from surface of unit	62.00 dBA

Conformance

Approvals	CSA, FCC Part 15 Class A, UL 1778
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
------	-----------

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.