

# ACSEW Control Operators: Push Button Components

## Momentary Contact. Explosionproof

Class I, Division 1 and 2, Groups B, C, D  
 Class II, Division 1 and 2, Groups E, F, G  
 Class III  
 NEMA 4, 7BCD, 9EFG

### Catalog Numbering Guide

**AE**  
 Appleton Explosionproof

**P**  
 Push Button

**D**  
 Dual Push Button:  
 Omit for Single Push Button

**B**  
 Color:  
 B - Black  
 R - Red  
 G - Green

**A**  
 Contact Arrangement:  
 A - 1 NO  
 B - 2 NO  
 C - 1 NC  
 D - 2 NC  
 E - 1 NO and 1 NC  
 F - 2 NO and 2 NC

**L**  
 Long Barrel:  
 Omit for Short Barrel



AEPBA



AEPDGRA

### Single Push Buttons

Contacts †	Button Color	Catalog Number	
		Short Barrel	Long Barrel
1 NO	Black	AEPBA	AEPBA-L
1 NO	Red	AEPRB	AEPRB-L
1 NO	Green	AEPGB	AEPGB-L
2 NO	Black	AEPBB	AEPBB-L
2 NO	Red	AEPRB	AEPRB-L
2 NO	Green	AEPGB	AEPGB-L
1 NC	Black	AEPBC	AEPBC-L
1 NC	Red	AEPRC	AEPRC-L
1 NC	Green	AEPGC	AEPGC-L
2 NC	Black	AEPBD	AEPBD-L
2 NC	Red	AEPRD	AEPRD-L
2 NC	Green	AEPGD	AEPGD-L
1 NO and 1 NC	Black	AEPBE	AEPBE-L
1 NO and 1 NC	Red	AEPRE	AEPRE-L
1 NO and 1 NC	Green	AEPGE	AEPGE-L
2 NO and 2 NC	Black	AEPBF	AEPBF-L
2 NO and 2 NC	Red	AEPRF	AEPRF-L
2 NO and 2 NC	Green	AEPGF	AEPGF-L

### Dual Push Buttons

Contacts †	Button Color	Catalog Number	
		Short Barrel	Long Barrel
2 NO	Green/Red	AEPDGRB	AEPDGRB-L
2 NO	Black/Black	AEPDBBB	AEPDBBB-L
2 NC	Green/Red	AEPDGRD	AEPDGRD-L
2 NC	Black/Black	AEPDBBD	AEPDBBD-L
1 NO and 1 NC	Green/Red	AEPDGRE	AEPDGRE-L
1 NO and 1 NC	Black/Black	AEPDBBE	AEPDBBE-L
2 NO and 2 NC	Green/Red	AEPDGRF	AEPDGRF-L
2 NO and 2 NC	Black/Black	AEPDBBF	AEPDBBF-L

NOTE: Use long barrel devices on enclosure applications with cover thickness exceeding 7/8 inch.  
 For legend plates, see Options, Accessories and Nameplates. All Operators are 3/4" NPSM.  
 † NO = Normally Open; NC = Normally Closed.