

**Product datasheet**  
Characteristics

# LGL36400U31X

PowerPact L Circuit

Breaker, Micrologic 3.3, 400A, 3P, 600V, 18kA



## Main

Product or component type	Circuit breaker
Range of product	PowerPact L
Trip unit technology	Electronic standard Micrologic 3.3 LI
Breaking capacity code	G

## Complementary

Protection technology	Current limiter
[In] rated current	400 A
Poles description	3P
Breaking capacity	65 kA at 240 V AC 35 kA at 480 V AC 18 kA at 600 V AC
[Ue] rated operational voltage	600 V AC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
AWG gauge	AWG 2/0...500 kcmil (aluminium/copper) 2(cable(s))
Terminal identifier	AL600LS52K3
Height	11.3 in
Width	5.5 in
Depth	6.61 in

## Environment

product certifications	CCC CE CSA UL listed NMX
------------------------	--------------------------------------

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1132 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.