

I.D. PRO Plus®, Brady LS2000 and BradyMarker™ XC Plus Labels


**PRINTER MODEL**

PRO = ID PRO/PRO Plus

LS = LS2000

BMXC = BradyMarker XC Plus

ALL = All ID PRO, LS2000, BMXC



► **BRADYSLEEVE™ WIRE MARKING SLEEVES**

**WMS Series – Non-Shrink White Polyolefin (B-319)**

Part Number	Portable Printer Model	Sleeves Per Roll	Range of Wire Dia. Inch (mm)		Approx. Wire Gauge*	Sleeve Dimension Inch (mm)		Maximum Lines of Print (PRO/LS)	Maximum Characters Across	
			Min.	Max.		A	B		Large (PRO/LS)	Small (PRO/LS)
WMS-105-319	ALL	500	0.075 (1.90)	0.130 (3.30)	12-18	0.500 (12.70)	0.350 (8.90)	1/1	3/3	4/7
WMS-111-319	ALL	500	0.075 (1.90)	0.130 (3.30)	12-18	1.000 (25.40)	0.350 (8.90)	1/1	7/7	10/15
WMS-117-319	ALL	500	0.075 (1.90)	0.130 (3.30)	12-18	1.500 (38.10)	0.350 (8.90)	1/1	10/11	15/23
WMS-205-319	ALL	500	0.130 (3.30)	0.235 (5.97)	8-10	0.500 (12.70)	0.500 (12.70)	2/2	3/3	4/7
WMS-211-319	ALL	500	0.130 (3.30)	0.235 (5.97)	8-10	1.000 (25.40)	0.500 (12.70)	2/2	7/7	10/15
WMS-217-319	ALL	500	0.130 (3.30)	0.235 (5.97)	8-10	1.500 (38.10)	0.500 (12.70)	2/2	10/11	15/23
WMS-411-319	ALL	500	0.235 (5.97)	0.375 (9.50)	3-6	1.000 (25.40)	0.750 (19.05)	4/4	7/7	10/15
WMS-417-319	ALL	500	0.235 (5.97)	0.375 (9.50)	3-6	1.500 (38.10)	0.750 (19.05)	4/4	10/11	15/23
WMS-611-319	ALL	250	0.375 (9.50)	0.540 (13.72)	2/0-2	1.000 (25.40)	1.000 (25.40)	6/6	7/7	10/15
WMS-617-319	ALL	250	0.375 (9.50)	0.540 (13.72)	2/0-2	1.500 (38.10)	1.000 (25.40)	6/6	10/11	15/23

**WMS Series – Heat-Shrink White Polyolefin (B-321)**

Part Number	Portable Printer Model	Sleeves Per Roll	Range of Wire Dia. Inch (mm)		Approx. Wire Gauge*	Sleeve Dimension Inch (mm)		Maximum Lines of Print (PRO/LS)	Maximum Characters Across	
			Min.	Max.		A	B		Large (PRO/LS)	Small (PRO/LS)
WMS-105-321	ALL	500	0.075 (1.90)	0.130 (3.30)	12-18	0.500 (12.70)	0.350 (8.90)	1/1	3/3	4/7
WMS-111-321	ALL	500	0.075 (1.90)	0.130 (3.30)	12-18	1.000 (25.40)	0.350 (8.90)	1/1	7/7	10/15
WMS-117-321	ALL	500	0.075 (1.90)	0.130 (3.30)	12-18	1.500 (38.10)	0.350 (8.90)	1/1	10/11	15/23
WMS-205-321	ALL	500	0.130 (3.30)	0.235 (5.97)	8-10	0.500 (12.70)	0.500 (12.70)	2/2	3/3	4/7
WMS-211-321	ALL	500	0.130 (3.30)	0.235 (5.97)	8-10	1.000 (25.40)	0.500 (12.70)	2/2	7/7	10/15
WMS-217-321	ALL	500	0.130 (3.30)	0.235 (5.97)	8-10	1.500 (38.10)	0.500 (12.70)	2/2	10/11	15/23
WMS-411-321	ALL	500	0.235 (5.97)	0.375 (9.50)	3-6	1.000 (25.40)	0.750 (19.05)	4/4	7/7	10/15
WMS-417-321	ALL	500	0.235 (5.97)	0.375 (9.50)	3-6	1.500 (38.10)	0.750 (19.05)	4/4	10/11	15/23
WMS-611-321	ALL	250	0.375 (9.50)	0.540 (13.72)	2/0-2	1.000 (25.40)	1.000 (25.40)	6/6	7/7	10/15
WMS-617-321	ALL	250	0.375 (9.50)	0.540 (13.72)	2/0-2	1.500 (38.10)	1.000 (25.40)	6/6	10/11	15/23

**WMS Series – Self-Extinguishing White Polyolefin (B-322)**

Part Number	Portable Printer Model	Sleeves Per Roll	Range of Wire Dia. Inch (mm)		Approx. Wire Gauge*	Sleeve Dimension Inch (mm)		Maximum Lines of Print (PRO/LS)	Maximum Characters Across	
			Min.	Max.		A	B		Large (PRO/LS)	Small (PRO/LS)
WMS-105-322	ALL	500	0.075 (1.90)	0.130 (3.30)	12-18	0.500 (12.70)	0.350 (8.90)	1/1	3/3	4/7
WMS-111-322	ALL	500	0.075 (1.90)	0.130 (3.30)	12-18	1.000 (25.40)	0.350 (8.90)	1/1	7/7	10/15
WMS-117-322	ALL	500	0.075 (1.90)	0.130 (3.30)	12-18	1.500 (38.10)	0.350 (8.90)	1/1	10/11	15/23
WMS-205-322	ALL	500	0.130 (3.30)	0.235 (5.97)	8-10	0.500 (12.70)	0.500 (12.70)	2/2	3/3	4/7
WMS-211-322	ALL	500	0.130 (3.30)	0.235 (5.97)	8-10	1.000 (25.40)	0.500 (12.70)	2/2	7/7	10/15
WMS-217-322	ALL	500	0.130 (3.30)	0.235 (5.97)	8-10	1.500 (38.10)	0.500 (12.70)	2/2	10/11	15/23
WMS-411-322	ALL	500	0.235 (5.97)	0.375 (9.50)	3-6	1.000 (25.40)	0.750 (19.05)	4/4	7/7	10/15
WMS-417-322	ALL	500	0.235 (5.97)	0.375 (9.50)	3-6	1.500 (38.10)	0.750 (19.05)	4/4	10/11	15/23
WMS-611-322	ALL	250	0.375 (9.50)	0.540 (13.72)	2/0-2	1.000 (25.40)	1.000 (25.40)	6/6	7/7	10/15
WMS-617-322	ALL	250	0.375 (9.50)	0.540 (13.72)	2/0-2	1.500 (38.10)	1.000 (25.40)	6/6	10/11	15/23

\*Based on National Electric Code insulation measurement of THHN wire.