



### Overview

Lead time Usually in Stock



### Main

Nominal Input Voltage	200 V 208 V 230 V
Output voltage	230 V
Plug standard	IEC 60309 32 A 2P+E
Number of rack unit	2U
Cable length	10 ft (3.05 m)
Number of cables	1
Provided Equipment	Documentation CD Installation guide Rack Mounting brackets

### Physical

Color	Black
Height	3.50 in (8.9 cm)
Width	17.52 in (44.5 cm)
Depth	4.49 in (11.4 cm)
Net Weight	9.92 lb(US) (4.5 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted

### Input

Acceptable Input Voltage	220...240 V
Input current limits	32 A
Load Capacity	7360 VA
Input Frequency	50/60 Hz

### Output

Number of power socket outlets	16 IEC 60320 C13
--------------------------------	------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Conformance

Product Certifications	CE GOST IRAM MIC VDE
Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3

## Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available