



Low Voltage Relays

On/Off Relays

Product #	Volts, 60 Hz	Resistive Charge (A)	
	Without transformer		
	RC840	120/208/240	22
		347	18
	R841D1036	600	10
	With transformer		
	RC840T-120	120	22
	RC840T-240	208/240	22
	RC840T-347	347	18
R841C1151	600	10	




NOTE: Not recommended for fast-cycling modulated regulation (more than 6 cycles/hr).
 For fast-cycling heating equipment use triac relay.
 Meant for external installation only. For installation inside heaters, refer to the options table of the concerned product series.

Triac Relays

Product #	Volts, 60 Hz	Input Signal	Resistive Charge (A)	
	Without transformer			
	RT850	100 to 347	4-32VDC, 24VAC	23
	CCT-25-1-C1	208/240/347	3-32VDC, 24VAC	25
	CCT-30-1-C2	48-600	3-32VDC, 24VAC	30
	With transformer			
	RT850T-240	208/240	19.2/24VAC	23
	RT850T-347	347	24VAC	23
	CCT-25-1-C2-T	208/240/277/347	14.4/16.6/19.2/24VAC	25

NOTE: Meant for external installation only. For installation inside heaters, refer to the options table of the concerned product series.

Universal Guards

Product #	Description
	F29-0143 Clear plastic thermostat guard Inside dimension: 6 3/8 in. (length), 3 1/2 in. (height), 3 in. (depth)
	F29-0198 Clear plastic thermostat guard Inside dimension: 8 1/4 in. (length), 5 3/8 in. (height), 3 1/2 in. (depth)
	F29-0193 Metal thermostat guard Inside dimension: 6 in. (length), 3 13/16 in. (height), 3 1/8 in. (depth)